



Electric Automation
Automation specialists

Artikel-Nr.: CR-M048AC4
Code: 1SVR405613R5000

CR-M048AC4 Pluggable interface relay 4c/o, A1-
A2=48VAC, 250V/6A

Kaufen von Electric Automation Network



Paket Level 1 Breite:	114 mm
Paket Level 1 Höhe:	61 mm
Paket Level 1 Länge:	50 mm
Paket Level 1 Brutto-Gewicht:	0,35 kg
Paket Level 1-EAN:	4013614373510

Technische

Funktion:	Steckbare Miniatur-interface-relais CR-M
Sub-Funktion:	Relais w/a built in LED
Ausgabe:	4 c/o (SPDT) Kontakte
Ausgangssignal:	250 V / 6 A
Rated Control Supply Voltage (U _s):	48 V AC

Umwelt

RoHS Status:	Nach der EU-Richtlinie 2011/65/EG
--------------	-----------------------------------

Zertifikate und Erklärungen (Dokument-Nummer)

CCC-Zertifikat:	CCC_2014010303720193
CSA-Zertifikat:	CSA_2735700
cUR-Zertifikat:	cUR_E244330
Konformitätserklärung - CE:	1SAD938501-0159
EAC Zertifikat:	EAC_RU_C-PL.ME77.B.01873
GOST-Zertifikat:	GOST_POCC_DE.AB76.D02256
LR-Zertifikat:	LR_05_20002_E3
RMRS-Zertifikat:	RMRS_12.04008.250
RoHS-Informationen:	1SAA981040-4404
UR Zertifikat:	UR_E244330
VDE-Zertifikat:	VDE_40040327

Klassifikationen

Objekt-Classification Code:	K
ETIM 4:	EC001437 - Schalt-relais
ETIM 5:	EC001437 - Schalt-relais
UNSPSC:	39121500
eClass:	7.0 27371601