



Electric Automation
Automation specialists

Riferimento: IPM1G
Codice: 1SBV001102R1823

Interruttore a pedale IPM1G

Acquista da Electric Automation Network



IPM1G Foot Switch

Ordering

| | |
|-------------------------|---------------|
| EAN: | 3471522009012 |
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85369085 |

Dimensions

| | |
|---------------------|----------|
| Product Net Weight: | 0.130 kg |
|---------------------|----------|


Container Information

| | |
|-------------------------------|---------------|
| Package Level 1 Units: | 1 piece |
| Package Level 1 Width: | 103 mm |
| Package Level 1 Height: | 77 mm |
| Package Level 1 Length: | 36 mm |
| Package Level 1 Gross Weight: | 0.13 kg |
| Package Level 1 EAN: | 3471522009012 |

Environmental

| | |
|--------------------------|--|
| Ambient Air Temperature: | Operation -10 ... +70 °C Storage -25 ... +80 °C |
|--------------------------|--|

Additional Information

| | |
|---|--|
| Action Type of the Contact Element (acc. to IEC 60947-5-1): | snap action contacts |
| Actuation Torque: | acc. to IEC 60947-5-1 Min. 1.20 N·m |
| Base Color: | Black |
| Connecting terminals (delivered in open position): | M3 x 0.5 screw with Phillips head  1 and washer |
| Contact Element Form (acc. to IEC 60947-5-1): | C |
| Conventional Free-air Thermal Current (I_{th}): | acc. to IEC 60947-5-1, $q = 40\text{ °C}$ 15.0 A |
| Cover Color: | grey |
| Degree of Protection: | acc. to IEC 60529 IP40 |
| Electrical Durability: | 100000 |
| IIT Publishing Status: | Level 0 - Information enabled |
| Mechanical Durability: | 10 million |
| Number of Auxiliary Contacts NC: | 1 |
| Number of Auxiliary Contacts NO: | 1 |
| Operating Angle of the Foot Switch Pedal: | 2 to 4 ° |
| Operating Format: | free movement |
| Product Main Type: | Foot Switches |
| Product Name: | Foot Switch |
| Rated Impulse Withstand Voltage (U_{imp}): | 1 kV |
| Rated Insulation Voltage (U_i): | acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 250 V |
| Rated Operational Current AC (I_e): | (250 V) 50 / 60 Hz 3 A |
| Rated Operational Current DC (I_e): | (230 V) 0.06 A |
| Resistance Between Contacts: | 30 mΩ |
| Standards: | IEC 61058-1 |

Certificates and Declarations (Document Number)

| | |
|------------------------------------|-----------------|
| Data Sheet, Technical Information: | 1SBC001699R1002 |
| Declaration of Conformity - CE: | 1SBD250883C2000 |

Classifications

| | |
|---------|------------------------------------|
| ETIM 4: | EC001829 - Position switch modular |
| ETIM 5: | EC001829 - Position switch modular |
| UNSPSC: | 39121500 |