

CAPICORDA A COMPRESSIONE SECONDO DIN 46234



per cavi in rame



Sezione Conduttore mm ²	Ø Vite mm	Tipo	Dimensioni mm					Imballo standard/minimo	Utensili Oleodinamici	
			Øi	d	L	B	a		HT 120 ed utensili e teste della linea 130 kN	ECM-HSD
95:120	8	Q 120-8	16,5	8,4	44,0	24,0	22,0	100/25		
	10	Q 120-10	16,5	10,5	44,0	24,0	22,0	100/25		
	12	Q 120-12	16,5	13,0	44,0	24,0	22,0	100/25		
	16	Q 120-16	16,5	17,0	48,0	28,0	22,0	50/25		
120:150	10	Q 150-10	19,0	10,5	50,0	30,0	24,0	50/25		
	12	Q 150-12	19,0	13,0	50,0	30,0	24,0	50/25		
	16	Q 150-16	19,0	17,0	50,0	30,0	24,0	50/25		
150:185	10	Q 185-10	21,0	10,5	50,0	36,0	28,0	40/20		
	12	Q 185-12	21,0	13,0	50,0	36,0	28,0	40/20		
	16	Q 185-16	21,0	17,0	50,0	36,0	28,0	30/15		
185:240	10	Q 240-10	23,5	10,5	56,0	38,0	32,0	15/15		
	12	Q 240-12	23,5	13,0	56,0	38,0	32,0	15/15		
	16	Q 240-16	23,5	17,0	56,0	38,0	32,0	15/15		

Altre dimensioni sono fornibili su richiesta

Capicorda speciali fornibili a richiesta.