



This outdoor vertical cooling unit, CUON, with a IP 55 protection degree, is available in many different sizes for different cooling requirements. This means that the right cooling solution can be chosen easily. Smart energy management reduces energy consumption with up to 23% compared to traditional solutions. The cooling unit is easy to install and is also available in stainless steel for harsh environments.

Description: High performance cooling unit for vertical installation. CUON is the air conditioning solution for critical environments, when the air conditioner is installed outdoors. The unit is external mounted in order to maximize space inside the enclosure. Common to all models is the self cleaning condenser coil, which eliminates the necessity for an air filter, avoiding standard maintenance. The thermostat is inside the unit and is adjustable between 25 °C and 45 °C with the Electronic Key-Pad (CUK01), which is available as an accessory. The factory setting is 35 °C. The cooling unit can also be supplied with a mechanically adjustable thermostat upon request. Ozone friendly refrigerant R134a.

Type of connection: Terminal included.

Material: Galvanized steel powder coated. The items ending in "SS" are manufactured from stainless steel AISI 304. Stainless steel AISI 316 is available on request.

Temperature limits inside: +25 °C to +45 °C.

Temperature limits outside: -40 °C to +55 °C.

Protection: IP 55 | TYPE 4, 4X.

Finish: RAL 7035 for the galvanized steel versions.

IP 55 | TYPE 4, 4X



CUON

Outdoor mounted cooling units



HOFFMAN

CONNECT AND PROTECT

H	W	D	Cooling capacity L35L35 (W)	Cooling capacity L35L50 (W)	Power	Power supply (V/ph/Hz)	Max. running current (A)	Starting current (A)	Pre-fuse (A)	Side cabinet fan flow (m³/h)	Noise level (dB)	Weight (kg)	Item no.
634	314	235	550 - 580	410 - 430	320 - 390	230 / 1 / 50 - 60	2.1	7.5	15	195	61	25.56	CUON05502
634	314	235	850 - 900	620 - 700	420 - 600	230 / 1 / 50 - 60	3.9	20	15	390	64	30.00	CUON08502
906	410	272	1100 - 1150	840 - 890	510 - 650	230 / 1 / 50 - 60	3.6	18	15	580	65	48.89	CUON10502
906	410	272	1500 - 1600	1200 - 1280	750 - 825	230 / 1 / 50 - 60	5.2	28	15	580	65	51.11	CUON15002
999	409	286	1500	1200	890	400 - 3 - 50 / 460 - 3 - 60	2.37	20	15	580	65	53.33	CUON15004
996	409	286	2100 - 2200	1750 - 1850	1120 - 1240	230 / 1 / 50 - 60	6.3	34	15	580	69	53.33	CUON21002
996	409	286	2100	1800	1200	400-3-50 / 460-3-60	3.62	22	15	930	69	53.33	CUON21004
1211	511	356	4000 - 4100	3000 - 3300	1730 - 1950	230 / 1 / 50 - 60	8.3	35	15	1300	70	88.89	CUON40502
1211	511	356	4050	3260	1950	400 - 3 - 50 / 460 - 3 - 60	5.96	19	15	1300	70	94.44	CUON40504
634	314	235	550 - 580	410 - 430	320 - 390	230 / 1 / 50 - 60	2.1	7.5	15	195	61	25.56	CUON05502SS
634	314	235	850 - 900	620 - 700	420 - 600	230 / 1 / 50 - 60	3.9	20	15	390	64	30.00	CUON08502SS
906	410	272	1100 - 1150	840 - 890	510 - 650	230 / 1 / 50 - 60	3.6	18	15	580	65	48.89	CUON10502SS
906	410	272	1500 - 1600	1200 - 1280	750 - 825	230 / 1 / 50 - 60	5.2	28	15	580	65	51.11	CUON15002SS
999	409	286	1500	1200	890	400 - 3 - 50 / 460 - 3 - 60	2.37	20	15	580	65	53.33	CUON15004SS
999	409	286	2100 - 2200	1750 - 1850	1120 - 1240	230 / 1 / 50 - 60	6.3	34	15	580	69	53.33	CUON21002SS
999	409	286	2100	1800	1200	400 - 3 - 50 / 460 - 3 - 60	3.62	22	15	930	69	53.33	CUON21004SS
1211	511	356	4000 - 4100	3000 - 3300	1730 - 1950	230 / 1 / 50 - 60	8.3	35	15	1300	70	88.89	CUON40502SS
1211	511	356	4050	3260	1950	400 - 3 - 50 / 460 - 3 - 60	5.96	19	15	1300	70	94.44	CUON40504SS

Note: The items ending in "SS" are manufactured from stainless steel AISI 304. Stainless steel AISI 316 is available on request.

CUON

Outdoor mounted cooling units



HOFFMAN

CONNECT AND PROTECT