

SFM

SWING FRAME MIDDLE MOUNTED



Description: Full height swing frame for 19" components allowing left and right hand opening with grip over the full height. Can be used in MultiFlex enclosures. Hinges designed to give extra build-in depth. Adjustable top hinge for square mounting of the swing frame. Rigid W-shaped frame profile for heavy equipment. Zinc plated frame for direct earthing of the mounted components. Full access to the enclosure aperture can be acquired by the standard fitted 180° hinges. For mounting use transversal support bars SFB. Depth support and easy cable routing is achieved with depth mounting plate SFMP. Adjustable in depth by steps of 12.5mm. Vertical profiles, 2mm and horizontal profiles, 3mm.

Lock: Double-bit 3mm espagnolette (other lock options possible).

Material: Frame zinc plated steel. Panels: 2mm steel plate.

Finish: RAL 7035 structured powder coating.

Pack quantity: 1 swing frame with hinges.

Mounting requirement: SFM for 800mm, 1000mm wide MultiFlex enclosures. Add SFB for mounting in a MultiFlex enclosure.

For					
U	H	H1	H2	H3	Item no.
27	1400	1203	1267	1337	SFM278
31	1600	1381	1445	1515	SFM318
36	1800	1603	1667	1737	SFM368
40	2000	1781	1845	1915	SFM408
45	2200	2003	2067	2137	SFM458