



STARTER PKZ2



Powering Business Worldwide™

Part no.

**PKZ2/
S(110V50HZ,120V60HZ)**

Article no.

063570

Delivery programme

Product range			PKZ2 basic unit up to 40 A - PRODUCT DISCONTINUATION IN 2012
Basic function			Motor protection System protection
Rated uninterrupted current	I_u	A	40

Approvals

Product Standards	UL 508; CSA-C22.2 No. 14; IEC60947-4-1; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL listed, CSA certified
Specially designed for NA	No

Technical data ETIM 4.0

Rated operation power at AC-3, 400 V		kWh	20
With integrated auxiliary switch			No
Rated permanent current I_u		A	40
With integrated under voltage release			No
Number of poles			3
Degree of protection (IP)			IP00
Connection type main current circuit			Screw connection

Additional product information (links)

AWA1280-0876 Motor-protective circuit-breaker	
	AWA1280-0876 Motor-protective circuit-breaker
AWB1210-1485 PKZ2 motor-protective circuit-breakers, overload monitoring of EEx e motors	
	AWB1210-1485 PKZ2 motor-protective circuit-breakers, overload monitoring of EEx e motors
Motor starters and "Special Purpose Ratings" for the North American market	http://www.moeller.net/binary/ver_techpapers/ver953en.pdf
Busbar Component Adapters for modern Industrial control panels	http://www.moeller.net/binary/ver_techpapers/ver960en.pdf