



## Built-in optical sensor

**Part no.**

**Z-DS/S-E**

**Article no.**

**111457**



Powering Business Worldwide™

### Technical data ETIM 4.0

|   |  |     |                |
|---|--|-----|----------------|
| Rated operating voltage                           |  | V   | 0              |
| Mounting depth                                    |  | mm  | 0              |
| Mounting type                                     |  |     | -              |
| Max. fluorescent lamp load (parallel-compensated) |  | V·A | 0              |
| Max. fluorescent lamp load (duo circuit)          |  | V·A | 0              |
| Max. fluorescent lamp load                        |  | V·A | 0              |
| Max. conductor length light sensor                |  | m   | 0              |
| Max. filament bulb load                           |  | W   | 0              |
| Max. switching current (p.f. = 0.6)               |  | A   | 0              |
| Rated operating voltage light sensor              |  | V   | 230            |
| Width in space units                              |  |     | 0              |
| Rated frequency                                   |  | Hz  | 0              |
| Mounting method light sensor                      |  |     | Flush mounting |
| Protection class light sensor                     |  |     | III            |
| Setting range brightness value                    |  | lx  | 2000           |
| Rated switch current                              |  | A   | 0              |
| Protection type (IP)                              |  |     | -              |
| Push button input                                 |  |     | No             |
| Degree of protection (IP) light sensor            |  |     | IP65           |
| With programmable overnight shutoff               |  |     | No             |