



Door, IP40, for HxW=2000x600mm

Part no. XVTL-D-6-20

Catalog No. 114650

EL-Nummer (Norway) 2460065

Delivery program

Product range		Control centres XVTL
Basic function		Combination enclosures
Product function		Accessories
Accessories		Doors
Single unit/Complete unit		Modular system
Description		Closed Single wing door 3-point turn lock with roller lever lock
Material		Sheet steel 1.25 mm
Surface finish		Polyester powder coating RAL 7035, light grey RAL 9016, traffic white
Information about equipment supplied		Including screws
Protection type		IP55
Suitable for width		600
Suitable for height		2000

Technical data ETIM 5.0

Cabinet enclosures (EG000011) / Door/operating panel (switchgear cabinet) (EC000747)		
Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Door (electrical cabinet) / Door/operating panel (enclosure) (ecl@ss8-27-18-22-04 [ACN614007])		
Model		Stop door
Version as glazed door		No
Version as door for disconnecting switch interlocking		No
Width	mm	593
Height	mm	1940
Depth	mm	40
EMC-version		Yes
Material		Steel
Type of surface		With powder coating
Colour		Grey
Degree of protection (IP)		IP55