DATASHEET - +IZMX-CAS403-2500



Cassette 2500A, IZMX403

Powering Business Worldwide*

Part no. +IZMX-CAS403-2500 Catalog No. 122787

Delivery program

Delivery program			
Product range			Accessories
Accessories			Withdrawable units
Accessories			Cassettes
			Equipment supplied: arcing chamber cover, coding to basic device
Rated current	In	Α	2500
Pole			3
For use with			IZMX403W INX403W
Instructions			With control circuit terminals according to ordered options.
Information about equipment supplied			with arcing chamber cover
Notes			
With control terminals according to the ordered options.			

Design verification as per IEC/EN 61439

•		
Technical data for design verification		
Operating ambient temperature min.	°C	-25
Operating ambient temperature max.	°C	70

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Chassis part power circuit breaker (EC002043)					
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Chassis part circuit breaker (ecl@ss10.0.1-27-37-04-22 [ACN955011])					
Rated current In	Α	2500			
Number of poles		3			
Version as busbar adapter		No			
Version as built-in device		Yes			
Type of electrical connection of main circuit		Rail connection			