



Connection 3p horizontal/vertical, 3200A

Part no. IZMX-THV403-3200
 Catalog No. 122911

EL-Nummer (Norway) 0004357109

Delivery program

Product range			Accessories
Accessories			Main terminal kits
Accessories			Horizontal and vertical connections
			Main terminals are not supplied as standard with the basic devices and cassettes. Each set contains the connections for top and bottom. 3 pole = 6 off; 4 pole = 8 off
Rated current	I_n	A	800 - 3200
Pole			3
For use with			IZMX40...4...08... IZMX40...4...10... IZMX40...4...12... IZMX40...4...16... IZMX40...4...20... IZMX40...4...25... IZMX40...4...32... INX40...4...08... INX40...4...10... INX40...4...12... INX40...4...16... INX40...4...20... INX40...4...25... INX40...4...32...
Information about equipment supplied			Main terminals are not supplied as standard with the basic devices and cassettes. Each set includes the connections for top and bottom. 3-pole= 6 connections; 4-pole= 8 connections, including accessories for mounting on the flanged circuit-breaker connection.

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Connection vane/phase spreader (EC002019)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Connection vane/phase spreader (ecl@ss10.0.1-27-37-13-05 [ACN990012])			
Suitable for number of poles			3