


Part no. IN63N3-63W
Catalog No. 124208

Delivery program

Product range			Air circuit-breakers/switch-disconnectors
Product range			Open switch-disconnectors
Current Range			4000 to 6300 A
Protective function			without protection
Installation type			Withdrawable
Construction size			IN63
Standard/Approval			IEC
Number of poles			3 pole
Degree of Protection			IP20, IP55 with protective cover
Rated current = rated uninterrupted current	$I_n = I_u$	A	6300
up to 440 V 50/60 Hz	I_{cm}	kA	217
t = 1 s	I_{cw}	kA	85
t = 3 s	I_{cw}	kA	65
Notes			
Including rear connection main terminals and secondary terminal blocks according to ordered breaker options.			
Note concerning the product			
Cassette needs to be ordered separately.			

Technical data

General

Standards			IEC/EN 60947
Ambient temperature			
Storage	θ	°C	-40 - +70
Operating (open)		°C	-25 - +70
Mounting position			
Utilization category			B
Degree of Protection			IP20, IP55 with protective cover
Direction of incoming supply			as required

Main conducting paths

Rated current = rated uninterrupted current	$I_n = I_u$	A	6300
Rated uninterrupted current at 50 °C	I_u	A	6200
Rated uninterrupted current at 60 °C	I_u	A	5600
Rated uninterrupted current at 70 °C	I_u	A	5100
Rated impulse withstand voltage	U_{imp}	V AC	8000
Rated operational voltage	U_e	V AC	690
Use in IT electrical power networks up to U = 440 V	I_{IT}	kA	88888888
Overvoltage category/pollution degree			III/3
Rated insulation voltage	U_i	V	1000

Switching capacity

Rated short-circuit making capacity	I_{cm}		
up to 440 V 50/60 Hz	I_{cm}	kA	217
up to 690 V 50/60 Hz	I_{cm}	kA	187

Operating times		
Closing delay via spring release	ms	35
Break times	ms	40
Total opening delay via shunt release	ms	40
Total opening delay via undervoltage release	ms	35/70
Maximum operating frequency		
Maximum operating frequency	Operations/h	60
Heat dissipation at rated current I_n		
Fixed mounting	W	620
Withdrawable units (switch with cassette)	W	1550

Weight

Fixed mounting		
3-pole	kg	125
4-pole	kg	163
Withdrawable		
3-pole	kg	157
4-pole	kg	200
Cassette		
3 pole	kg	103
4 pole	kg	103

Terminal capacities

Copper bar		
Fixed mounting		
Black	mm	6 x 10 x 100
Withdrawable units		
Black	mm	6 x 10 x 100

Permissible continuous current for circuit-breakers operating in switchboards at various internal ambient temperatures. The switchboard's internal ambient temperature should be estimated using the calculation methods of IEC regulation.

Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature min.	°C	-25
Operating ambient temperature max.	°C	70

Dimensions

