



Signalling switch ON-OFF, 8W



Powering Business Worldwide™

Part no. **+IZMX-AS88**  
 Catalog No. **124345**

## Delivery program

Product range			Accessories
Accessories			Auxiliary contact
Accessories			Standard auxiliary switch for On-Off signaling
			Standard auxiliary switch for On-Off signaling. The basic device already contains two changeover contacts. Two additional changeover contacts possible.
For use with			IZMX40... INX40...
			8 changeover contacts

## Technical data

### Rated breaking capacity

Inductive load			
250 V AC		A	10
125 V DC		A	0.5
250 V DC		A	0.25

## Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

## Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ecl@ss8.1-27-37-13-02 [AKN342010])			
Number of contacts as change-over contact			8
Number of contacts as normally open contact			0
Number of contacts as normally closed contact			0
Rated operation current I <sub>e</sub> at AC-15, 230 V		A	10
Type of electric connection			Flat plug-in connection
Model			Half-integrated
Mounting method			Other