



Switch-disconnector, status signal OFF



Powering Business Worldwide™

Part no. IZMX-LCS  
 Catalog No. 124351  
 Eaton Catalog No. IZMX-LCS

### Delivery program

Accessories			Auxiliary contact
Accessories			Operational readiness indicator
For use with			IZMX16..., IZMX40... INX16..., INX40...
Instructions			For signaling availability
			OFF message

### Technical data

#### Rated breaking capacity

Inductive load			
250 V AC		A	10
125 V DC		A	0.5
250 V DC		A	0.25

### Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

### Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ecI@ss10.0.1-27-37-13-02 [AKN342013])			
Number of contacts as change-over contact			1
Number of contacts as normally open contact			0
Number of contacts as normally closed contact			0
Number of fault-signal switches			
Rated operation current I <sub>e</sub> at AC-15, 230 V		A	10
Type of electric connection			Flat plug-in connection
Model			Integrable
Mounting method			Other
Lamp holder			