



Switch disconnecter, low voltage, 1600 A, AC 400 V, NH4a, AC22B, 3P, IEC, plate mounting, 3-phase simultaneous switching

Catalog No. EBH403TM2-16

### Delivery program

Product range			Fuse accessory
Basic function			Switch disconnecter
Field of application			low voltage
Rated current	I	A	1600
Rated voltage			AC 400 V
Construction size			NH4a
Utilization category			AC22B
Description			mounting plate type 3-phase simultaneous switching M12 screws
Protection			IP20
Number of poles			3P
usable for size/applications			NH4a fuse-links
Standard/Approval			IEC
Shape			Horizontal
Standards/Regulations			IEC 60947-1 IEC 60947-3

### Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Fuse switch disconnecter (EC001040)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnecter (ecl@ss10.0.1-27-37-14-01 [AKF058013])			
Version as main switch			No
Version as safety switch			No
Max. rated operation voltage Ue AC		V	690
Rated permanent current Iu		A	1600
Rated operation power at AC-23, 400 V		kW	640
Conditioned rated short-circuit current Iq		kA	50
Rated short-time withstand current Icw		kA	50
Suitable for fuses			NH4a
Number of poles			3
With error protection			No
Type of electrical connection of main circuit			Screw connection
Cable entry			Other
Equipped with connectors			Yes
Suitable for ground mounting			No
Suitable for front mounting 4-hole			Yes
Suitable for busbar mounting			No
Type of control element			Cover grip
Position control element			Front side
Motor drive optional			No
Motor drive integrated			No
Version as emergency stop installation			No
Degree of protection (IP), front side			IP30