



**Lead-through terminal for B-type arresters, 125A, 500V AC/DC, overvoltage category III**

**Part no. SPB-D-125**  
**Catalog No. 248145**

### Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	$I_n$	A	0
Heat dissipation per pole, current-dependent	$P_{vid}$	W	0
Equipment heat dissipation, current-dependent	$P_{vid}$	W	0
Static heat dissipation, non-current-dependent	$P_{vs}$	W	0
Heat dissipation capacity	$P_{diss}$	W	0
Operating ambient temperature min.		°C	-40
Operating ambient temperature max.		°C	85
			0

### Technical data ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)			
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss10.0.1-27-14-35-02 [AKE327013])			
Device fitting			Other
Additional equipment			Other
Attached at delivery			No
Assembly width (TE)			1
Number of contacts as normally open contact			
Number of contacts as normally closed contact			
Number of contacts as change-over contact			
Number of fault-signal switches			0
Rated switch current		A	125
Rated voltage		V	500
Voltage type for actuating			AC/DC
With auto test for earth leakage function			No
Suitable for max. number of poles main contact unit (total)			1
Suitable for max. current main contact unit		A	12