Flange, knockout 2x M16, 4x M20, 2x M25/16, 2x M40/25, 3x M50/32, HxWxD=116x329x23mm



Part no. FL4-5 021982 EL Number 4132333

(Norway)	
General specifications	
Product name	Eaton xEnergy Safety Ci flange plate
Part no.	FL4-5
EAN	4015080219828
Product Length/Depth	115 millimetre
Product height	23 millimetre
Product width	330 millimetre
Product weight	0.272 kilogram
Compliances	RoHS conform
Product Tradename	xEnergy Safety Ci
Product Type	Accessories
Product Sub Type	Flange plate
Delivery program	
Туре	Accessory for basic enclosures Basic enclosure xEnergy Safety Ci
Model	Cable screw gland
Accessory/spare part type	Flanges
Technical Data - Mechanical	
Shape	Straight
Unit type	Modular system
Surface protection	Untreated
Material	Plastic
Degree of protection	Other
Number of connector holes	0
Cable entry type	2 x M40/25 2 x M25/16 4 x M20 3 x M50/32 2 x M16
Thickness	4 mm
Thread type	Metric
Suitable for cable diameter - min	0 mm
Suitable for cable diameter - max	0 mm
Suitable for nominal thread (PG) - min	16
Suitable for nominal thread (PG) - max	50
Additional information	
Features	Pre-stamping

Technical data ETIM 9.0

Special features

Used with

Distribution boards (EG000023) / Gland plate for enclosure/cabinet (EC000211)

Electric engineering, automation, process control engineering / Electrical installation, device / Electrical distribution system (including small distribution board) / Gland plate for small distribution boards/switchgear cabinets (ecl@ss13-27-14-24-21 [ADI315012])

Model		Cable screw gland	
Туре		Straight	
Width	mm	330	

Sponge-rubber, captive gasket Quick mounting using wedge-lock fasteners

(included as standard)
375 mm (enclosure dimensions)

Basic enclosure xEnergy Safety Ci

Accessory for basic enclosures

Height	mm	23
Thickness	mm	4
Material		Plastic
Surface protection		Untreated
Degree of protection (NEMA)		Other
Pre-stamping		Yes
Number of connector holes		0
Suitable for cable diameter	mm	0 - 0
Thread type		Metric
Suitable for nominal thread metric/PG		16 - 50
Gland plate type according to SEN 280901		