

Cable grommet, PG36

Part no. **KT36**
033896
 EL Number **4132345**
 (Norway)

General specifications		
Product name		Eaton xEffect Accessories cable grommet PG
Part no.		KT36
EAN		4015080338963
Product Length/Depth		20 millimetre
Product height		55 millimetre
Product width		55 millimetre
Product weight		0.023 kilogram
Compliances		RoHS conform
Product Tradename		xEffect Accessories
Product Type		Cable grommet
Product Sub Type		PG
Delivery program		
Type		General switchboard accessory
Model		Closed
Accessory/spare part type		Cable management Cable grommets
Color		Gray
Technical Data - Mechanical		
Bore diameter		48 mm
Surface finishing		Similar RAL 7035
Surface protection		Other
Material		Plastic Soft PVC Cadmium- and lead-free
Material quality		Polyvinyl chloride (PVC)
Degree of protection		IP66
Number of cables - min		1
Number of cables - max		1
Operating temperature - min		-5 °C
Operating temperature - max		40 °C
For outer cable diameter - min		18 mm
For outer cable diameter - max		40 mm
For wall thickness - min		2 mm
For wall thickness - max		8 mm
Cable entry type		PG 36 Round
Opening diameter		48 mm
Thread size		0
Suitable for cable diameter - min		18 mm
Suitable for cable diameter - max		40 mm
Additional information		
Features		Watertight Gastight
Used with		For wall thickness 2 - 8 mm NYM/NYY 4 core, 10 mm ² - 70 mm ²

Technical data ETIM 9.0

Cable and wire entry systems (EG000009) / Cable entry sleeve (EC000879)

Electric engineering, automation, process control engineering / Electrical installation, device / Cable gland / Additional components cable gland (ec|@ss13-27-14-08-07 [AHD200002])

Model			Closed
Suitable for cable gland			No
Cable entry			Round
Number of cables			1 - 1
Suitable for cable diameter		mm	18 - 40
Bore diameter		mm	48
For wall thickness		mm	2 - 8
Thread size (metric)			0
Thread size PG			36
Total length		mm	20
With strain relief			No
Shrink technique			No
Angle model			No
Material			Plastic
Material quality			Polyvinyl chloride (PVC)
Surface protection			Other
Halogen free			No
Colour			Grey
Gastight			Yes
Fire resistant			No
Watertight			Yes
Degree of protection (IP)			IP66
Operating temperature		°C	-5 - 40