

Padlocking feature, for PKZ0/4 in the enclosure



**Part no.** SVB-PKZ0-CI  
**035129**  
**EL Number** 4355156  
**(Norway)**

General specifications		
Product name		Eaton Moeller® series SVB Accessory Padlocking feature
Part no.		SVB-PKZ0-CI
EAN		4015080351290
Product Length/Depth		33 millimetre
Product height		98 millimetre
Product width		79 millimetre
Product weight		0.06 kilogram
Certifications		CSA-C22.2 No. 14 UL 508 CSA Class No.: 3211-05 UL CE CSA File No.: 165628 IEC/EN 60947-4-1 UL File No.: E36332 CSA UL Category Control No.: NLRV
Product Tradename		SVB
Product Type		Accessory
Product Sub Type		Padlocking feature
Features & Functions		
Locking facility		Lockable in the 0 (Off) position
Material		Polycarbonate
General information		
Suitable as		Main switch to IEC/EN 60204
Climatic environmental conditions		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		55 °C
Design verification		
Equipment heat dissipation, current-dependent P <sub>vid</sub>		0 W
Heat dissipation capacity P <sub>diss</sub>		0 W
Heat dissipation per pole, current-dependent P <sub>vid</sub>		0 W
Rated operational current for specified heat dissipation (I <sub>n</sub> )		0 A
Static heat dissipation, non-current-dependent P <sub>vs</sub>		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			Not applicable.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Padlock barrier for switch (EC002051)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Padlock barrier for switch (ecl@ss13-27-37-13-07 [ACN994016])			
Max. number of padlocks			3
Suitable for shackle diameter		mm	2 - 4
With label area			No
Material			Polycarbonate (PC)