

Illuminated selector switch actuator, momentary, 45°, 25 × 25 mm, 2 positions, With thumb-grip, White, with VS anti-rotation tab, without light elements, With base, W2x4,6d; max. 30 V, 1 W

Part no. **Q25LWK1-WS**  
**040658**

<b>General specifications</b>		
Product name		Eaton Moeller® series RMQ16 Illuminated selector switch actuator
Part no.		Q25LWK1-WS
EAN		4015080406587
Product Length/Depth		75 millimetre
Product height		25 millimetre
Product width		25 millimetre
Product weight		0.017 kilogram
Certifications		UL 508 UL File No.: E29184 CSA File No.: 46552 UL Category Control No.: NKCR CSA-C22.2 No. 14-05 CE IEC/EN 60947-5 UL IEC/EN 60947 CSA Class No.: 3211-03 CSA
Product Tradename		RMQ16
Product Type		Illuminated selector switch actuator
Product Sub Type		None
Catalog Notes		Filament bulb or LED needs to be ordered separately
<b>Features &amp; Functions</b>		
Bezel color		Black
Bezel material		Plastic
Design		With thumb-grip
Fitted with:		VS anti-rotation tab
<b>General information</b>		
Degree of protection		NEMA 1
Degree of protection (front side)		IP65
Lifespan, mechanical		3,000,000 Operations
Opening diameter		16 mm
Operating frequency		1800 Operations/h
Operating torque		0.2 N·m
Overvoltage category		III
Pollution degree		3
Product category		RMQ16
Size		Front dimensions: 25 × 25 mm
Rated impulse withstand voltage (Uimp)		800 V AC
Suitable for		Illumination
Switching angle		45 °
Terminal capacity		0.5 - 1.0 mm <sup>2</sup>
Terminal size		2.8 x 0.8 mm to DIN 46247 and IEC 60760, Fast-on connectors 2.8 x 0.8 mm to DIN 46244, Blade terminal
Type		Illuminated selector switch actuator
<b>Ambient conditions, mechanical</b>		
Mounting position		As required
Shock resistance		Mechanical, According to IEC/EN 60068-2-27 40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
<b>Climatic environmental conditions</b>		

Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		60 °C
Ambient operating temperature (enclosed) - min		25 °C
Ambient operating temperature (enclosed) - max		40 °C
Climatic proofing		Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
<b>Electrical rating</b>		
Rated insulation voltage (Ui)		250 V
Rated operational voltage (Ue) at AC - max		24 V
<b>Actuator</b>		
Actuator color		Black
Actuator function		Spring-return Momentary
Actuator type		Toggle
Number of switch positions		2
<b>Contacts</b>		
Control circuit reliability		1 failure per 5,000,000 switching operations (statistically determined, at 5 V DC/1 mA) 1 failure per 10,000,000 switching operations (Statistically determined, at 24 V DC/5 mA)
<b>Communication</b>		
Connection to SmartWire-DT		No
<b>Design verification</b>		
Equipment heat dissipation, current-dependent Pvid		0 W
Heat dissipation capacity Pdiss		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
Rated operational current for specified heat dissipation (In)		0 A
Static heat dissipation, non-current-dependent Pvs		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		Not applicable.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Front element for selector switch (EC000222)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for selector switches (ecl@ss13-27-37-12-13 [AKF031019])		
Number of switch positions		2

Type of control element			Toggle
Suitable for illumination			Yes
Colour control element			Black
Colour indicator light cap			White
Construction type lens			Square
Hole diameter		mm	16
Width opening		mm	0
Height opening		mm	0
Switching function latching			No
Spring-return			Yes
With front ring			No
Material front ring			Plastic
Colour front ring			Black
Degree of protection (IP), front side			IP65
Degree of protection (NEMA)			1