

## Selector switch, 3 positions, white, maintained

**Part no.**                    **Q25WK3R**  
**072373**

<b>General specifications</b>		
Product name		Eaton Moeller® series RMQ16 Changeover switch
Part no.		Q25WK3R
EAN		4015080723738
Product Length/Depth		65 millimetre
Product height		25 millimetre
Product width		25 millimetre
Product weight		0.015 kilogram
Certifications		CSA Class No.: 3211-03 UL File No.: E29184 CSA File No.: 46552 IEC/EN 60947-5 CSA UL Category Control No.: NKCR UL 508 CE UL IEC/EN 60947 CSA-C22.2 No. 14-05
Product Tradename		RMQ16
Product Type		Changeover switch
Product Sub Type		None
Catalog Notes		Use of insulated ferrule ISH 2,8 > 24 V AC/DC recommended Use of insulated ferrule ISH 2,8 > 50 V AC or 120 V DC is mandatory, even on unused blade terminals
<b>Features &amp; Functions</b>		
Bezel color		Black
Bezel material		Plastic
Design		With thumb-grip
Fitted with:		Front ring VS anti-rotation tab
<b>General information</b>		
Degree of protection		NEMA 1
Degree of protection (front side)		IP65
Lifespan, mechanical		3,000,000 Operations
Opening diameter		16 mm
Operating frequency		1800 Operations/h
Operating torque		0.2 N·m
Overvoltage category		III
Pollution degree		3
Product category		RMQ16
Size		Front dimensions: 25 × 25 mm
Rated impulse withstand voltage (Uimp)		800 V AC
Switching angle		45 °
Terminal capacity		0.5 - 1.0 mm <sup>2</sup>
Terminal size		2.8 x 0.8 mm to DIN 46244, Blade terminal 2.8 x 0.8 mm to DIN 46247 and IEC 60760, Fast-on connectors
Type		Selector switch actuator
<b>Ambient conditions, mechanical</b>		
Mounting position		As required
Shock resistance		40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27
<b>Climatic environmental conditions</b>		
Ambient operating temperature - min		-25 °C

Ambient operating temperature - max		60 °C
Ambient operating temperature (enclosed) - min		25 °C
Ambient operating temperature (enclosed) - max		40 °C
Climatic proofing		Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
<b>Electrical rating</b>		
Rated insulation voltage (Ui)		250 V
Rated operational voltage (Ue) at AC - max		24 V
<b>Actuator</b>		
Actuator color		White
Actuator function		Maintained Switching function latching
Actuator type		Toggle
Number of switch positions		3
<b>Contacts</b>		
Control circuit reliability		1 failure per 5,000,000 switching operations (statistically determined, at 5 V DC/1 mA) 1 failure per 10,000,000 switching operations (Statistically determined, at 24 V DC/5 mA)
<b>Communication</b>		
Connection to SmartWire-DT		No
<b>Design verification</b>		
Equipment heat dissipation, current-dependent Pvid		0 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
Rated operational current for specified heat dissipation (In)		0 A
Static heat dissipation, non-current-dependent Pvs		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		Not applicable.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Front element for selector switch (EC000222)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for selector switches (ecl@ss13-27-37-12-13 [AKF031019])		
Number of switch positions		3
Type of control element		Toggle

Suitable for illumination			No
Colour control element			White
Colour indicator light cap			Other
Construction type lens			Square
Hole diameter		mm	16
Width opening		mm	0
Height opening		mm	0
Switching function latching			Yes
Spring-return			No
With front ring			Yes
Material front ring			Plastic
Colour front ring			Black
Degree of protection (IP), front side			IP65
Degree of protection (NEMA)			1