

**Standard auxiliary contact, 1 N/O, 1 NC, Can be retrofitted on the right side of motor-protective circuit-breakers, Screw terminals**

**Part no.** NHI11-PKZ0  
**072896**  
**EL Number** 4355131  
**(Norway)**

<b>General specifications</b>		
Product name		Eaton Moeller® series NHI Accessory Standard auxiliary contact
Part no.		NHI11-PKZ0
EAN		4015080728962
Product Length/Depth		68 millimetre
Product height		90 millimetre
Product width		15 millimetre
Product weight		0.033 kilogram
Certifications		UL UL Category Control No.: NLRV CE CSA CSA Class No.: 3211-05 UL 508 CSA-C22.2 No. 14 IEC/EN 60947-4-1 UL File No.: E36332 CSA File No.: 165628
Product Tradename		NHI
Product Type		Accessory
Product Sub Type		Standard auxiliary contact
Catalog Notes		Can be retrofitted on the right side of motor-protective circuit-breakers
<b>Features &amp; Functions</b>		
Electric connection type		Screw connection
Features		Interlocked opposing contacts
<b>General information</b>		
Lifespan, electrical		50,000 Operations
Model		Top mounting
Mounting method		Side mounting
Overtoltage category		III
Pollution degree		3
Product category		Accessories
Rated impulse withstand voltage (Uimp)		6000 V AC
Used with		Motor protective circuit-breaker
<b>Climatic environmental conditions</b>		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		55 °C
<b>Terminal capacities</b>		
Terminal capacity (solid/flexible with ferrule)		0.75 - 1.5 mm <sup>2</sup>
Terminal capacity (solid/stranded AWG)		18 - 14, Screw terminals
<b>Electrical rating</b>		
Rated operational current (Ie)		1 A at AC-15, 440 V 500 V
Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V		3.5 A
Rated operational current (Ie) at AC-15, 380 V, 400 V, 415 V		2 A
Rated operational current (Ie) at DC-13, 110 V		0.5 A
Rated operational current (Ie) at DC-13, 220 V, 230 V		0.25 A
Rated operational current (Ie) at DC-13, 24 V		2 A
Rated operational current (Ie) at DC-13, 60 V		1 A
Rated operational voltage (Ue) at AC - max		500 V
Rated operational voltage (Ue) at DC - max		250 V

Safe isolation		440 V, Between auxiliary contacts and main contacts, According to EN 61140
Short-circuit protection rating without welding		10 A gG/gL, Fuse, Auxiliary contacts
<b>Switching capacity</b>		
Switching capacity (auxiliary contacts, general use)		1 A, 250 V DC, (UL/CSA) 5 A, 600 V AC, (UL/CSA)
Switching capacity (auxiliary contacts, pilot duty)		Q300, DC operated (UL/CSA) A600, AC operated (UL/CSA)
<b>Communication</b>		
Connection type		Screw connection
<b>Contacts</b>		
Control circuit reliability		< 2 λ, < 1 failure at 100,000,000 Operations (at U# = 24 V DC, Umin = 17 V, Imin = 5.4 mA)
Number of contacts (change-over contacts)		0
Number of contacts (normally closed contacts)		1
Number of contacts (normally open contacts)		1
<b>Design verification</b>		
Equipment heat dissipation, current-dependent Pvid		0 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		0.04 W
Rated operational current for specified heat dissipation (In)		3.5 A
Static heat dissipation, non-current-dependent Pvs		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ecl@ss13-27-37-13-02 [AKN342018])		
Number of contacts as change-over contact		0
Number of contacts as normally open contact		1
Number of contacts as normally closed contact		1
Number of fault-signal switches		0
Rated operation current Ie at AC-15, 230 V	A	3.5
Type of electric connection		Screw connection
Model		Clip-on

Mounting method		Side mounting
Lamp holder		None