

Undervoltage release PKZ0(4), PKE, AC, 400 V 50 Hz, Screw terminals,
When ordered with basic unit



Part no. **+U-PKZ0(400V50HZ)**
073257

General specifications		
Product name		Eaton Moeller® series U-PKZ0 Accessory Undervoltage Release
Part no.		+U-PKZ0(400V50HZ)
EAN		4015080732570
Product Length/Depth		68 millimetre
Product height		90 millimetre
Product width		24 millimetre
Product weight		0.129 kilogram
Certifications		CE marking CSA certified UL File No.: E36332 UL 508 UL Listed IEC 60947-4-1 UL Category Control No.: NLRV CSA File No.: 165628 CSA-C22.2 No. 14 CSA Class No.: 3211-05
Product Tradename		U-PKZ0
Product Type		Accessory
Product Sub Type		Undervoltage Release
Features & Functions		
Electric connection type		Screw connection
General information		
Suitable for		Motor safety switch
Voltage type		AC
Magnet system		
Rated control supply voltage (Us) at AC, 50 Hz - min		400 V
Rated control supply voltage (Us) at AC, 50 Hz - max		400 V
Rated control supply voltage (Us) at AC, 60 Hz - min		0 V
Rated control supply voltage (Us) at AC, 60 Hz - max		0 V
Rated control supply voltage (Us) at DC - min		0 V
Rated control supply voltage (Us) at DC - max		0 V
Contacts		
Number of contacts (change-over contacts)		0
Number of contacts (normally closed contacts)		0
Number of contacts (normally open contacts)		0

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Under voltage coil (EC001022)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Undervoltage trip (ecl@ss13-27-37-04-17 [AKF015018])		
Rated control supply voltage AC 50 Hz	V	400 - 400
Rated control supply voltage AC 60 Hz	V	0 - 0
Rated control supply voltage DC	V	0 - 0
Voltage type for actuating		AC
Type of electric connection		Screw connection
Number of contacts as normally open contact		0
Number of contacts as normally closed contact		0
Number of contacts as change-over contact		0
Delayed		No
Suitable for power circuit breaker		No

Suitable for off-load switch		No
Suitable for motor safety switch		Yes
Suitable for overload relay		No