

Terminal block, 1 pole, 175A, 10 output terminals



Part no. BPZ-KB-10/175
102715
EL Number 2459291
(Norway)

General specifications		
Product name		Eaton xEnergy Basic LV systems Low voltage switchgear
Part no.		BPZ-KB-10/175
EAN		4015081025756
Product Length/Depth		43 millimetre
Product height		71 millimetre
Product width		45 millimetre
Product weight		0.23 kilogram
Compliances		RoHS conform
Certifications		IEC 60 947 -7 -1 UL 1059
Product Tradename		xEnergy Basic
Product Type		LV systems
Product Sub Type		Low voltage switchgear
Delivery program		
Amperage rating		175 A
Number of poles		Single-pole
Technical Data - Electrical		
Voltage rating at AC Cu (CSA) - max		600 V AC
Voltage rating at AC Cu (IEC) - max		1000 V AC
Voltage rating at AC Cu (UL) - max		600 V AC
Voltage rating at DC Cu (IEC) - max		1500 V DC
Rated peak withstand current		30 kA
Rated operation current (Ie) Cu (CSA)		175 A
Rated operation current (Ie) Cu (IEC)		175 A
Rated operation current (Ie) Cu (UL)		175 A
Rated short-time withstand current (Icw)		11 kA
Technical Data - Mechanical		
Mounting method		Flush mounting Floor standing distribution board Surface mounting
Mounting position		Universal
Degree of protection		IP20
Number of clamp positions per pole		11
Number of clamping units per pole		11
Terminal capacity (single/multi-wire)		2.5 mm ² - 10 mm ² (outgoing, fine wire (with sleeve)) 6 - 2/0 AWG (incoming) 14 - 6 AWG (outgoing) 14 - 8 AWG (outgoing, fine wire (with sleeve)) 2.5 mm ² - 16 mm ² (outgoing) 16 mm ² - 70 mm ² (incoming) 6 - 1 AWG (incoming, fine wire (with sleeve)) 16 mm ² - 50 mm ² (incoming, fine wire (with sleeve))
Conductor cross section (solid, solid-strand) - min		2.5 mm ²
Conductor cross section (solid, solid-strand) - max		70 mm ²
Clamp material		Plain Brass
Torque rating		6 Nm - 10 Nm / 53.1 lbf - 88.5 lbf (incoming). 3 Nm - 4 Nm / 26.5 lbf - 35.4 lbf (outgoing)
Housing color		Light gray (RAL 7035)
Housing material		PA66
Design verification as per IEC/EN 61439 - technical data		

Heat deflection temperature		100 °C
Additional information		
Comparative tracking index (CTI)		600 V
Flame classification (UL 94)		V-0
Functions		Additional equipment
Special features		Clicks on DIN-rail or on base plate. Save time on wiring. Save 80% on space used. Modular construction, 1-4 pole Systems can be built with several blocks. Material, hexagon socket set screw: Steel Zinc plated (Hexagon socket set screw, Surface finish)

Technical data ETIM 9.0

Energy distribution systems (EG000015) / Distributor assembly terminal blocks (EC001894)			
Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Distributor assembly terminal blocks (ecI@ss13-27-40-06-09 [AC0381016])			
Height		mm	71
Width		mm	45
Depth		mm	43
Max. rated current		A	175
Number of poles			1
Conductor cross section flexible (fine-strand) with cable end sleeve		mm ²	2.5 - 70
Conductor cross section solid (solid, stranded)		mm ²	2.5 - 70
Number of clamp positions per pole			11
With PE-rail			No
With N-rail			No