

Roller plunger, center fixing



Part no. **LS-XZRS**
114025
EL Number **4315224**
(Norway)

General specifications	
Product name	Eaton Moeller® series LS Roller plunger
Part no.	LS-XZRS
EAN	4015081134472
Product Length/Depth	45 millimetre
Product height	25 millimetre
Product width	25 millimetre
Product weight	0.028 kilogram
Certifications	UL File No.: E29184 UL CSA File No.: 012528 IEC/EN 60947-5 CSA-C22.2 No. 14 CSA Class No.: 3211-03 CE UL 508 UL Category Control No.: NKCR CSA
Product Tradename	LS
Product Type	Roller plunger
Product Sub Type	None
Features & Functions	
Features	The operating head can be rotated 90° to enable adaptation to the specified approach direction
Functions	For mounting in enclosure wall or mounting plate drilling M18 x 1
General information	
Product category	Roller plunger, centre fixing
Type	Operating heads
Climatic environmental conditions	
Ambient operating temperature - min	-40 °C
Ambient operating temperature - max	70 °C
Actuator	
Actuator type	Roller cam
Design verification	
Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdis	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	0 A
Static heat dissipation, non-current-dependent Pvs	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Please enquire
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			Not applicable.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Sensors (EG000026) / Drive head for position switches/hinge switches (EC001483)			
Electric engineering, automation, process control engineering / Sensor technology, safety-related sensor technology / Mechanical switch (sensor technology) / Drive head for position switches (ecl@ss13-27-27-06-04 [BAA083017])			
Type of control element			Roller cam