



Starter kit, EASY819-AC-RC, EASY800-USB-CAB and easySoft-Pro

Part no. **EASY-BOX-819-AC-USB**
Catalog No. **116560**

Delivery program

| | | | |
|-----------------------------|--|---|-------------------------|
| Product range | | | Control relay easyRelay |
| Basic function | | | Starter kit |
| Heat dissipation at 24 V DC | | W | 10 |

Technical data

General

| | | | |
|-----------|--|--|--|
| Standards | | | EN 55011, EN 55022, IEC/EN 61000-4, IEC 60068-2-6, IEC 60068-2-27 |
| Approvals | | | CSA UL EAC |
| Mounting | | | Top-hat rail IEC/EN 60715, 35 mm or screw fixing using fixing brackets ZB4-101-GF1 (accessories) |

Terminal capacities

| | | | |
|-----------------------|--|-----------------|-----------------------|
| Solid | | mm ² | 0.2/4 (AWG 22 - 12) |
| Flexible with ferrule | | mm ² | 0.2/2.5 (AWG 22 - 12) |

Climatic environmental conditions

| | | | |
|-------------------------------|--|-----|---|
| Operating ambient temperature | | °C | In accordance with IEC 60068-2-1, -25 - +55 |
| Condensation | | | Take appropriate measures to prevent condensation |
| relative humidity | | % | in accordance with IEC 60068-2-30, IEC 60068-2-78 5 - 95 |
| Air pressure (operation) | | hPa | 795 - 1080 |

Ambient conditions, mechanical

| | | | |
|--|-------------|---------|--|
| Protection type (IEC/EN 60529, EN50178, VBG 4) | | | IP20 |
| Vibrations | | Hz | In accordance with IEC 60068-2-6 constant amplitude 0.15 mm: 10 - 57 constant acceleration 2 g: 57 - 150 |
| Mechanical shock resistance (IEC/EN 60068-2-27) semi-sinusoidal 15 g/11 ms | | Impacts | 18 |
| Drop to IEC/EN 60068-2-31 | Drop height | mm | 50 |
| Free fall, packaged (IEC/EN 60068-2-32) | | m | 1 |
| Mounting position | | | Vertical or horizontal |

Electromagnetic compatibility (EMC)

| | | | |
|---|--|----|-------------------------------|
| Overvoltage category/pollution degree | | | III/2 |
| Electrostatic discharge (ESD) | | | |
| applied standard | | | according to IEC EN 61000-4-2 |
| Air discharge | | kV | 8 |
| Contact discharge | | kV | 6 |
| Immunity to line-conducted interference to (IEC/EN 61000-4-6) | | V | 10 |

Insulation resistance

| | | | |
|---|--|--|--------------------------------------|
| Clearance in air and creepage distances | | | EN 50178, UL 508, CSA C22.2, No. 142 |
| Insulation resistance | | | EN 50178 |

Power supply

| | | | |
|-----------------------------|--|---|----|
| Heat dissipation at 24 V DC | | W | 10 |
|-----------------------------|--|---|----|

Design verification as per IEC/EN 61439

| | | | |
|--|------------------|---|----|
| Technical data for design verification | | | |
| Rated operational current for specified heat dissipation | I _n | A | 0 |
| Heat dissipation per pole, current-dependent | P _{vid} | W | 0 |
| Equipment heat dissipation, current-dependent | P _{vid} | W | 0 |
| Static heat dissipation, non-current-dependent | P _{vs} | W | 10 |

| | | | |
|--|-------------------|----|--|
| Heat dissipation capacity | P _{diss} | W | 0 |
| Operating ambient temperature min. | | °C | -25 |
| Operating ambient temperature max. | | °C | 55 |
| IEC/EN 61439 design verification | | | |
| 10.2 Strength of materials and parts | | | |
| 10.2.2 Corrosion resistance | | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | | Meets the product standard's requirements. |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects | | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | | Meets the product standard's requirements. |
| 10.2.5 Lifting | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | | Meets the product standard's requirements. |
| 10.3 Degree of protection of ASSEMBLIES | | | Meets the product standard's requirements. |
| 10.4 Clearances and creepage distances | | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | | Is the panel builder's responsibility. |
| 10.9 Insulation properties | | | |
| 10.9.2 Power-frequency electric strength | | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | | Is the panel builder's responsibility. |
| 10.12 Electromagnetic compatibility | | | Is the panel builder's responsibility. |
| 10.13 Mechanical function | | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 7.0

| | | | |
|--|--|---|----------|
| PLC's (EG000024) / Logic module (EC001417) | | | |
| Electric engineering, automation, process control engineering / Control / Programmable logic control (SPS) / Logic module (ecl@ss10.0.1-27-24-22-16 [AKE539014]) | | | |
| Supply voltage AC 50 Hz | | V | 85 - 264 |
| Supply voltage AC 60 Hz | | V | 85 - 264 |
| Supply voltage DC | | V | 0 - 0 |
| Voltage type of supply voltage | | | AC |
| Switching current | | A | 8 |
| Number of analogue inputs | | | 0 |
| Number of analogue outputs | | | 0 |
| Number of digital inputs | | | 12 |
| Number of digital outputs | | | 6 |
| With relay output | | | Yes |
| Number of HW-interfaces industrial Ethernet | | | 0 |
| Number of interfaces PROFINET | | | 0 |
| Number of HW-interfaces RS-232 | | | 0 |
| Number of HW-interfaces RS-422 | | | 0 |
| Number of HW-interfaces RS-485 | | | 0 |
| Number of HW-interfaces serial TTY | | | 0 |
| Number of HW-interfaces USB | | | 0 |
| Number of HW-interfaces parallel | | | 0 |
| Number of HW-interfaces Wireless | | | 0 |
| Number of HW-interfaces other | | | 3 |
| With optical interface | | | No |
| Supporting protocol for TCP/IP | | | No |

| | | |
|---|----|-------|
| Supporting protocol for PROFIBUS | | No |
| Supporting protocol for CAN | | No |
| Supporting protocol for INTERBUS | | No |
| Supporting protocol for ASI | | No |
| Supporting protocol for KNX | | No |
| Supporting protocol for MODBUS | | No |
| Supporting protocol for Data-Highway | | No |
| Supporting protocol for DeviceNet | | No |
| Supporting protocol for SUCONET | | No |
| Supporting protocol for LON | | No |
| Supporting protocol for PROFINET IO | | No |
| Supporting protocol for PROFINET CBA | | No |
| Supporting protocol for SERCOS | | No |
| Supporting protocol for Foundation Fieldbus | | No |
| Supporting protocol for EtherNet/IP | | No |
| Supporting protocol for AS-Interface Safety at Work | | No |
| Supporting protocol for DeviceNet Safety | | No |
| Supporting protocol for INTERBUS-Safety | | No |
| Supporting protocol for PROFIsafe | | No |
| Supporting protocol for SafetyBUS p | | No |
| Supporting protocol for other bus systems | | Yes |
| Radio standard Bluetooth | | No |
| Radio standard WLAN 802.11 | | No |
| Radio standard GPRS | | No |
| Radio standard GSM | | No |
| Radio standard UMTS | | No |
| IO link master | | No |
| Redundancy | | No |
| With display | | Yes |
| Degree of protection (IP) | | IP20 |
| Basic device | | Yes |
| Expandable | | Yes |
| Expansion device | | No |
| With timer | | Yes |
| Rail mounting possible | | Yes |
| Wall mounting/direct mounting | | Yes |
| Front build in possible | | No |
| Rack-assembly possible | | No |
| Suitable for safety functions | | No |
| Category according to EN 954-1 | | None |
| SIL according to IEC 61508 | | None |
| Performance level acc. EN ISO 13849-1 | | None |
| Appendant operation agent (Ex ia) | | No |
| Appendant operation agent (Ex ib) | | No |
| Explosion safety category for gas | | None |
| Explosion safety category for dust | | None |
| Width | mm | 107.5 |
| Height | mm | 90 |
| Depth | mm | 72 |

Additional product information (links)

Instruction leaflet "easy control relays" IL05013012Z (AWA2528-1979)

| | |
|--|---|
| Instruction leaflet "easy control relays" IL05013012Z (AWA2528-1979) | ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL05013012Z2010_11.pdf |
| Instruction leaflet "easy control relays" IL05013012Z (AWA2528-1979) | ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL05013012Z2018_02.pdf |

Manual "easy800 control relays" MN04902001Z (AWB2528-1423)

| | |
|---|---|
| Handbuch „Steuerrelais easy800“ MN04902001Z (AWB2528-1423) - Deutsch | ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN04902001Z_DE.pdf |
| Manual "easy800 control relays" MN04902001Z (AWB2528-1423) - English | ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN04902001Z_EN.pdf |
| Product overview (WEB) | http://www.eaton.eu/easy |