



**Mounting set IEC Busbar support SASY for MSW application 5 poles
WxH=800x450mm**

Part no. BPZ-BR/SASY/MSW/H-5/800

Catalog No. 120716

**EL-Nummer 2460992
(Norway)**

Delivery program

| | | | |
|----------------------------|--|----|---|
| Mounting type | | | Floor standing distribution board Surface mounted Flush mounted |
| Mounting position | | | horizontal |
| Device mounting positions | | | vertikal |
| Number of poles | | | 5 pole |
| Width | | mm | 800 |
| Height | | mm | 450 |
| Suitable for width | | mm | 800 |
| Colour | | | light gray (RAL 7035) |
| Devices that can be fitted | | | SASY |
| applicable for | | | IEC busbar support MSW assembly configuration |
| Assembling quantity | | | for single mounting |

Technical data ETIM 7.0

| | | | |
|---|--|----|----------------|
| Energy distribution systems (EG000015) / Distributor assembly busbars (EC001896) | | | |
| Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Distributor assembly busbars (ecl@ss10.0.1-27-40-06-10 [AC0383011]) | | | |
| Height | | mm | 448 |
| Width | | mm | 720 |
| Depth | | mm | 63 |
| With cover | | | Yes |
| Number of poles | | | 5 |
| Busbar distance | | mm | 60 |
| Busbar height | | mm | 30 |
| Busbar thickness | | mm | 5 |
| Max. rated current | | A | 400 |
| Short-circuit breaking capacity (Icw) | | kA | 0 |
| Busbar position | | | Centre central |