

**Variable frequency drive, 600 V AC, 3-phase, 3 kW, IP21, Radio interference suppression filter, OLED display, FR6**



**Part no. SPX003A1-5A4N1**

**125222**

**EL Number  
(Norway)**

**4100118**

<b>General specifications</b>		
Product name		Eaton SPX variable frequency drive
Part no.		SPX003A1-5A4N1
EAN		4015081228287
Product Length/Depth		558 millimetre
Product height		237 millimetre
Product width		195 millimetre
Product weight		18.5 kilogram
Certifications		Specification for general requirements: IEC/EN 61800-2 UL 508C UL Category Control No.: NMMS, NMMS2, NMMS7, NMMS8 UL File No.: E134360 CSA-C22.2 No. 14 CSA Class No.: 3211-06 RoHS, ISO 9001 UL report applies to both US and Canada UL Safety: EN 61800-5-1: 2003 IEC/EN61800-3 CE Certified by UL for use in Canada CUL IEC/EN61800-5 DNV IEC/EN 61800-3 RCM
Product Tradename		SPX
Product Type		Variable frequency drive
Product Sub Type		None
Catalog Notes		Assigned motor rating: For AC motors with internal and external ventilation with 50 Hz / 60 Hz Assigned motor rating: Overload cycle for 60 s every 600 s
<b>General information</b>		
Degree of protection		IP21 NEMA Other
Electromagnetic compatibility		1st and 2nd environments (according to EN 61800-3)
Fitted with:		Radio interference suppression filter Internal DC link IGBT inverter OLED display DC link choke
Frame size		FR6
Mounting position		Vertical
Product Category		Variable frequency drives
Protection		Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)
Radio interference class		C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.
Suitable for		Branch circuits, (UL/CSA)
<b>Climatic environmental conditions</b>		
Altitude		Max. 1000 m Max. 3000 m Above 1000 m with 1 % performance reduction per 100 m
Ambient operating temperature - min		-10 °C
Ambient operating temperature - max		50 °C
Ambient operating temperature at 150% overload - min		-10 °C
Ambient operating temperature at 150% overload - max		50 °C
Ambient storage temperature - min		-40 °C

Ambient storage temperature - max		70 °C
Climatic proofing		< 95 % relative humidity, no condensation, no corrosion, no dripping water
<b>Main circuit</b>		
Mains voltage - min		525 V
Mains voltage - max		690 V
Operating mode		U/f control Optional: Vector control with feedback (CLV) Sensorless vector control (SLV)
Output frequency - min		0 Hz
Output frequency - max		320 Hz
Output voltage (U2)		600 V AC, 3-phase 690 V AC, 3-phase
Rated control supply voltage		10 V DC (Us, max. 10 mA)
Rated frequency - min		45 Hz
Rated frequency - max		66 Hz
Rated operational current (Ie) at 110% overload		5.5 A
Rated operational current (Ie) at 150% overload		4.5 A
Rated operational power at 690 V, 50 Hz		3 kW
Rated operational power at 690 V, 50 Hz, 110% overload		4 kW
Rated operational voltage		600 V AC, 3-phase 690 V AC, 3-phase
Resolution		0.01 Hz (Frequency resolution, setpoint value)
Supply frequency		50/60 Hz
Switching frequency		1.5 kHz, 1 - 6 kHz adjustable, fPWM, Power section, Main circuit
System configuration type		AC supply systems with earthed center point
Voltage rating - max		690 V AC
<b>Motor rating</b>		
Assigned motor current IM at 690 V, 50 Hz, 110% overload		4.9 A
Assigned motor current IM at 690 V, 50 Hz, 150% overload		3.8 A
Assigned motor current IM at 690 V, 60 Hz, 110% overload		5.3 A
Assigned motor current IM at 690 V, 60 Hz, 150% overload		3.4 A
Assigned motor power at 690 V, 60 Hz		3 HP
Assigned motor power at 690 V, 60 Hz, 110% overload		5 HP
<b>Control circuit</b>		
Number of inputs (analog)		2 (parameterizable, 0 - 10 V DC, 0/4 - 20 mA)
Number of inputs (digital)		6 (parameterizable, max. 30 V DC)
Number of outputs (analog)		1
Number of outputs (digital)		1 (parameterizable, 48 V DC/50 mA)
Number of relay outputs		2 (parameterizable, N/O, 8 A (24 V DC) / 8 A (250 V AC) / 0,4 A (125 V DC))
Rated control voltage (Uc)		24 V DC (external, max. 250 mA)
<b>Communication</b>		
Communication interface		PROFIBUS-DP Modbus-TCP, optional BACnet/IP, optional CANopen®, optional DeviceNet, optional LonWorks, optional BACnet MS/TP, optional EtherCAT, optional Ethernet IP, optional Modbus-RTU, optional PROFINET, optional
Connection to SmartWire-DT		No
<b>Design verification</b>		
Equipment heat dissipation, current-dependent Pvid		75 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
Rated operational current for specified heat dissipation (In)		4.5 A
Static heat dissipation, non-current-dependent Pvs		0 W
Heat dissipation details		Operation (with 150 % overload)

10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.