DATASHEET - QSAN250/315/400A

General specifications Product name

Neutral conductor, 250/315/400A

Part no.

QSAN250/315/400A 1319480



Eaton QSA Accessory Neutral conductor

QSAN250/315/400A Part no. EAN 8711426773677 Product Length/Depth 215 millimetre Product height 40 millimetre Product width 160 millimetre Product weight 0.42 kilogram CE Compliances QSA **Product Tradename** Product Type Accessory Product Sub Type Neutral conductor **General information** Accessory/spare part type Neutral terminal Mounting method Side mounting Туре Direct neutral conductor Neutral conductor **Climatic environmental conditions** Ambient operating te Ambient operating te **Design verification** Equipment heat dissip Heat dissipation capa Heat dissipation per p Rated operational cu Static heat dissipatio 10.2.2 Corrosion resis 10.2.3.1 Verification o 10.2.3.2 Verification o 10.2.3.3 Resist. of insu 10.2.4 Resistance to u 10.2.5 Lifting 10.2.6 Mechanical im 10.2.7 Inscriptions 10.3 Degree of protec 10.4 Clearances and o 10.5 Protection again

Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	50 °C
Design verification	
Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdiss	0 W
Heat dissipation per pole, current-dependent Pvid	16 W
Rated operational current for specified heat dissipation (In)	400 A
Static heat dissipation, non-current-dependent Pvs	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility. The specifications for the switchgear must be observed.

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Accessories/spare parts for low-voltage switch technology (EC002498)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Component for low-voltage switching technology (accessories) (ecl@ss13-27-37-13-92 [AKN570018])

Type of accessory/spare part	Neutral to	erminal
Accessory	Yes	
Spare part	No	