

Soft starter, 4 A, 200 - 480 V AC, Us= 24 V AC/DC, Frame size FS1

Part no. **DS7-340SX004N0-N**
134847

EL Number
 (Norway) **4134260**

General specifications		
Product name		Eaton DS7 Soft starter
Part no.		DS7-340SX004N0-N
EAN		4015081316922
Product Length/Depth		94 millimetre
Product height		130 millimetre
Product width		45 millimetre
Product weight		0.35 kilogram
Compliances		CE Marked
Certifications		CSA Std. C22.2 No. 14-05 CSA Std. C22.2 No. 0-M91 UL 508 IEC 60947-4-2 EN 60947-4-2 UL File No.: E251034 CSA Class No.: 321106 CSA-C22.2 No 14-05 CSA22.2-14 CSA C-Tick GB 14048.6 IEC/EN 60947-4-2 CSA-C22.2 No 0-M91 CE UL UkrSEPRO CSA File No.: 2511305
Product Tradename		DS7
Product Type		Soft starter
Product Sub Type		None
Catalog Notes		Ambient Operating Temperature up to 60 at 2% derating per Kelvin temperature rise External Reversing starter solution required Regulator supply: External supply voltage
Features & Functions		
Fitted with:		Internal bypass contacts Internal bypass
Functions		Potential isolation between power and control sections Min. ramp time 1 s - fast switching (semiconductor contactor) Suppression of closing transients Single direction Soft start function Suppression of DC components for motors
General information		
Class		Other
Connection to SmartWire-DT		No
Degree of protection		IP20 NEMA 1
Frame size		FS1
Mains voltage - min		200 V
Mains voltage - max		480 V
Overvoltage category		II
Pollution degree		2
Radio interference class		Class B (EN 55011)
Suitable for		Branch circuits, (UL/CSA)
Type		Soft starter for three-phase loads
Voltage type		AC/DC
Ambient conditions, mechanical		
Mounting position		Vertical

Shock resistance		8 g, 11 ms, Mechanical
Vibration resistance		2M2 to EN 60721-3-2
Climatic environmental conditions		
Altitude		Above 1000 m with 1 % derating per 100 m Max. 2000 m
Ambient operating temperature - min		-5 °C
Ambient operating temperature - max		40 °C
Ambient storage temperature - min		-25 °C
Ambient storage temperature - max		60 °C
Climatic proofing		Damp heat, constant, to IEC 60068-2-3 Damp heat, cyclic, to IEC 60068-2-30
Main conducting paths		
Overload cycle		AC-53a: 3 - 5: 75 - 10
Rated operational current (Ie) at AC-53		4 A
Rated operational voltage (Ue) - min		230 V
Rated operational voltage (Ue) - max		480 V
Short-circuit protection rating		3 x 170M1359, Type „2“ coordination (additional with the fuses for coordination type „1“), Main conducting paths PKM0-4 (+ CL-PKZ0), Type “1” coordination, Main conducting paths
Supply frequency		50/60 Hz, fLN, Main circuit
Voltage rating - max		480 V
Motor rating		
Assigned motor power at 200/208 V, 60 Hz, 3-phase		0.75 HP
Assigned motor power at 220/230 V, 60 Hz, 3-phase		1 HP
Assigned motor power at 460/480 V, 60 Hz, 3-phase		2 HP
Rated operational power at 220/230 V, 50 Hz		0.75 kW
Rated operational power at 400 V, 50 Hz		1.5 kW
Terminal capacities		
Terminal capacity (flexible with ferrule)		2 x (0.75 - 2.5) mm ² , Control circuit cables 1 x (0.75 - 2.5) mm ² , Main cables 2 x (0.75 - 2.5) mm ² , Main cables 1 x (0.75 - 2.5) mm ² , Control circuit cables
Terminal capacity (solid)		2 x (0.75 - 2.5) mm ² , Control circuit cables 2 x (0.75 - 2.5) mm ² , Main cables 1 x (0.75 - 4) mm ² , Control circuit cables 1 x (0.75 - 4) mm ² , Main cables
Terminal capacity (solid/stranded AWG)		18 - 10, Main cables 18 - 10, Control circuit cables
Screwdriver size		PZ2, 1 x 6 mm, Terminal screw, Standard screwdriver 0.6 x 5.5 mm/1 x 6 mm, Terminal screws, Control circuit cables
Tightening torque		1.2 Nm, Screw terminals, Control circuit cables 1.2 Nm
Control circuit		
Current consumption		1.6 mA, Control circuit, Digital inputs, External 24 V 50 mA, Control circuit, Regulator supply
Drop-out time		350 ms, Control circuit, Digital Inputs, DC operated
Drop-out voltage		AC operated: 0 - 3 V, AC operated 0 - 3 V, DC operated
Pick-up time		250 ms at DC 250 ms at AC
Pick-up voltage		17.3 - 27 V DC 17.3 - 27 V AC
Rated control supply voltage (Us) at AC, 50 Hz - min		24 V
Rated control supply voltage (Us) at AC, 50 Hz - max		24 V
Rated control supply voltage (Us) at AC, 60 Hz - min		24 V
Rated control supply voltage (Us) at AC, 60 Hz - max		24 V
Rated control supply voltage (Us) at DC - min		24 V
Rated control supply voltage (Us) at DC - max		24 V
Input/Output		
Number of outputs		1 Relay Output (TOR)
Output voltage		24 V AC/DC

Protection			Finger and back-of-hand proof, Protection against direct contact
Rated control voltage (Uc)			24 V AC (-15 %/+10 %) 24 V AC 24 V DC 24 V DC (-15 %/+10 %)
Rated operational current (Ie) at AC-11			1 A
Soft start function			
Application			1-phase motors: No 3-phase motors: Yes Soft starting of three-phase asynchronous motors
Delay time			0 - 30 s, Soft start function, Ramp times
Ramp/run-up time			1 - 30 s
Start voltage			Min. 30 %, Soft start function, Start voltage = turn-off voltage Max. 100 %, Soft start function, Start voltage = turn-off voltage
Design verification			
Equipment heat dissipation, current-dependent Pvid			0.2 W
Heat dissipation capacity Pdis			0 W
Heat dissipation per pole, current-dependent Pvid			0 W
Rated operational current for specified heat dissipation (In)			4 A
Static heat dissipation, non-current-dependent Pvs			0.2 W
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Soft starter (EC000640)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Load breakout, motor breakout / Semiconductor motor controller or soft starter (ec1@ss13-27-37-09-07 [AC0300016])			
Rated operation current Ie at 40 °C Tu	A	4	
Rated operating voltage Ue	V	230 - 480	
Rated power three-phase motor, inline, at 230 V	kW	0.75	
Rated power three-phase motor, inline, at 400 V	kW	1.5	
Rated power three-phase motor, inside delta, at 230 V	kW	0	
Rated power three-phase motor, inside delta, at 400 V	kW	0	
Function		Single direction	
Internal bypass		Yes	
With display		No	

Torque control		No
Rated surrounding temperature without derating	°C	40
Rated control supply voltage AC 50 Hz	V	24 - 24
Rated control supply voltage AC 60 Hz	V	24 - 24
Rated control supply voltage DC	V	24 - 24
Voltage type for actuating		AC/DC
Integrated motor overload protection		No
Release class		Other
Degree of protection (IP)		IP20
Degree of protection (NEMA)		1