

Soft starter, 16 A, 200 - 480 V AC, 24 V DC, Frame size: FS2, Communication
Interfaces: SmartWire-DT



Part no. **DS7-34DSX016N0-D**
134948
EL Number **4137336**
(Norway)

General specifications		
Product name		Eaton DS7 Soft starter
Part no.		DS7-34DSX016N0-D
EAN		4015081317639
Product Length/Depth		126 millimetre
Product height		150 millimetre
Product width		45 millimetre
Product weight		0.4 kilogram
Certifications		CSA C-Tick CSA-C22.2 No 14-05 CSA22.2-14 UL GB 14048.6 IEC/EN 60947-4-2 UL 508 CE UkrSEPRO CSA-C22.2 No 0-M91 UL CSA
Product Tradename		DS7
Product Type		Soft starter
Product Sub Type		None
Catalog Notes		Ambient Operating Temperature up to 60 at 2% derating per Kelvin temperature rise External Reversing starter solution required Regulator supply: External supply voltage
Features & Functions		
Fault memory		8 Faults
Fitted with:		Internal bypass contacts Internal bypass
Functions		Suppression of DC components for motors Soft start function Potential isolation between power and control sections Single direction Min. ramp time 1 s - fast switching (semiconductor contactor) Current limitation, with PKE Suppression of closing transients
Interfaces		SmartWire-DT (built-in)
General information		
Class		Other
Connection to SmartWire-DT		Yes
Degree of protection		NEMA 1 IP20
Frame size		FS2
Mains voltage - min		200 V
Mains voltage - max		480 V
Overvoltage category		II
Pollution degree		2
Radio interference class		Class B (EN 55011)
Suitable for		Branch circuits, (UL/CSA)
Type		Soft starter for three-phase loads
Voltage type		DC
Ambient conditions, mechanical		
Mounting position		Vertical
Shock resistance		8 g, 11 ms, Mechanical

Vibration resistance			2M2 to EN 60721-3-2
Climatic environmental conditions			
Altitude			Max. 2000 m Above 1000 m with 1 % derating per 100 m
Ambient operating temperature - min			-5 °C
Ambient operating temperature - max			40 °C
Ambient storage temperature - min			-25 °C
Ambient storage temperature - max			60 °C
Climatic proofing			Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-3
Main conducting paths			
Overload cycle			AC-53a: 3 - 5: 75 - 10
Rated operational current (Ie) at AC-53			16 A
Rated operational voltage (Ue) - min			230 V
Rated operational voltage (Ue) - max			480 V
Short-circuit protection rating			3 x 170M1364, Type „2“ coordination (additional with the fuses for coordination type „1“), Main conducting paths PKM0-16 (+ CL-PKZ0), Type “1” coordination, Main conducting paths
Supply frequency			50/60 Hz, fLN, Main circuit
Voltage rating - max			480 V
Motor rating			
Assigned motor power at 200/208 V, 60 Hz, 3-phase			5 HP
Assigned motor power at 220/230 V, 60 Hz, 3-phase			5 HP
Assigned motor power at 460/480 V, 60 Hz, 3-phase			10 HP
Rated operational power at 220/230 V, 50 Hz			4 kW
Rated operational power at 400 V, 50 Hz			7.5 kW
Terminal capacities			
Terminal capacity (flexible with ferrule)			2 x (0.5 - 0.75) mm ² , Control circuit cables 2 x (0.75 - 10) mm ² , Main cables 1 x (0.5 - 1.5) mm ² , Control circuit cables 1 x (0.75 - 16) mm ² , Main cables
Terminal capacity (solid)			1 x (0.5 - 2.5) mm ² , Control circuit cables 1 x (0.75 - 16) mm ² , Main cables 2 x (0.75 - 10) mm ² , Main cables 2 x (0.5 - 1.0) mm ² , Control circuit cables
Terminal capacity (solid/stranded AWG)			18 - 14, Control circuit cables 18 - 6, Main cables
Terminal capacity (stranded)			1 x 16 mm ² , Main cables
Screwdriver size			PZ2, 1 x 6 mm, Terminal screw, Standard screwdriver 0.6 x 5.5 mm/1 x 6 mm, Terminal screws, Control circuit cables
Tightening torque			1.2 Nm, Screw terminals, Control circuit cables 3.2 Nm
Control circuit			
Current consumption			1.6 mA, Control circuit, Digital inputs, External 24 V 50 mA, Control circuit, Regulator supply
Drop-out time			350 ms, Control circuit, Digital Inputs, DC operated
Drop-out voltage			0 - 3 V, DC operated
Pick-up time			250 ms at DC
Pick-up voltage			17.3 - 27 V DC
Rated control supply voltage (Us) at AC, 50 Hz - min			0 V
Rated control supply voltage (Us) at AC, 50 Hz - max			0 V
Rated control supply voltage (Us) at AC, 60 Hz - min			0 V
Rated control supply voltage (Us) at AC, 60 Hz - max			0 V
Rated control supply voltage (Us) at DC - min			24 V
Rated control supply voltage (Us) at DC - max			24 V
Input/Output			
Number of outputs			2 Relay Outputs (TOR, Ready)
Output voltage			250 V AC (relay outputs)
Protection			Finger and back-of-hand proof, Protection against direct contact
Rated control voltage (Uc)			24 V DC (-15 %/+10 %) or via SmartWire-DT

			24 V DC
Rated operational current (Ie) at AC-11			1 A
Soft start function			
Application			1-phase motors: No 3-phase motors: Yes Soft starting of three-phase asynchronous motors
Current limitation			(0 - 8) x Ie, Soft start function
Delay time			0 - 30 s, Soft start function, Ramp times
Ramp/run-up time			1 - 30 s
Start voltage			Max. 100 %, Soft start function, Start voltage = turn-off voltage Min. 30 %, Soft start function, Start voltage = turn-off voltage
Design verification			
Equipment heat dissipation, current-dependent Pvid			0.8 W
Heat dissipation capacity Pdis			0 W
Heat dissipation per pole, current-dependent Pvid			0 W
Rated operational current for specified heat dissipation (In)			16 A
Static heat dissipation, non-current-dependent Pvs			0.8 W
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Soft starter (EC000640)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Load breakout, motor breakout / Semiconductor motor controller or soft starter (ecI@ss13-27-37-09-07 [ACO300016])			
Rated operation current Ie at 40 °C Tu		A	16
Rated operating voltage Ue		V	230 - 480
Rated power three-phase motor, inline, at 230 V		kW	4
Rated power three-phase motor, inline, at 400 V		kW	7.5
Rated power three-phase motor, inside delta, at 230 V		kW	0
Rated power three-phase motor, inside delta, at 400 V		kW	0
Function			Single direction
Internal bypass			Yes
With display			No
Torque control			No
Rated surrounding temperature without derating		°C	40

Rated control supply voltage AC 50 Hz	V	0 - 0
Rated control supply voltage AC 60 Hz	V	0 - 0
Rated control supply voltage DC	V	24 - 24
Voltage type for actuating		DC
Integrated motor overload protection		No
Release class		Other
Degree of protection (IP)		IP20
Degree of protection (NEMA)		1