



Connection cable, 4p, DC current, coupling M12 flat, plug, angled, L=1.5m



Powering Business Worldwide™

Part no. CSDR4A4CY2201.5-D
Catalog No. 136313
Alternate Catalog No. CSDR4A4CY2201P5-D
EL-Nummer (Norway) 0004315404

Delivery program

Basic function		Accessories
Accessories		Connecting cables
Length	mm	1500
Pin assignment		
Voltage type		DC
Number of poles		4 pole
Style output side		Plug, angled
Style input side		Coupling, straight
For use with		
For use with		DC sensors, 4 pole, 2, 3 or 4-wire connection, M12

Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature min.	°C	-25
Operating ambient temperature max.	°C	70

Technical data ETIM 7.0

Sensors (EG000026) / Sensor-actuator patch cord (EC001855)		
Electric engineering, automation, process control engineering / Cable, wire / Ready-made data cable / Assembled sensor actuator-line (ecl@ss10.0.1-27-06-03-11 [AFR601003])		
Number of poles		4
Type of electrical connection, field-sided		M12
Type of plug-in contact, field sided		Female (bus)
Positioning cable feed, field-sided		Straight
Type of electrical connection, box-sided		M12
Type of plug-in contact, box-sided		Male (plug)
Positioning cable feed, box-sided		Angled
Cable length	m	1.5
Material of cable sheath		Other
Halogen free		No
Colour cable sheath		Other
With LED indication		No
Screened		No
Type of cable		Multi-core
Vulcanize		No
Material contact body		Other
Material of contact surface		Other
Permitted cable outer temperature after assembling without vibration	°C	40 - 70
Permitted cable outer temperature during assembling/handling	°C	40 - 70
Rated current In	A	0
Rated voltage	V	0
Continuity resistor	mOhm	0
Degree of protection (IP)		Other

Approvals

Product Standards

CE marking