

Overload relay, Separate mounting, Earth-fault protection: none, Ir= 20 - 100 A, 1 N/O, 1 N/C

Part no. ZEB150-100/KK

136508

EL Number
(Norway)

4137377

General specifications	
Product name	Eaton Moeller® series ZEB Electronic overload Relay
Part no.	ZEB150-100/KK
EAN	4015081332885
Product Length/Depth	140.5 millimetre
Product height	120 millimetre
Product width	56 millimetre
Product weight	0.84 kilogram
Certifications	CSA-C22.2 No. 14 UL File No.: E1230 UL CSA Class No.: 3211-03 UL Category Control No.: NKCR IEC/EN 60947 CSA File No.: 2290956 CSA CE IEC/EN 60947-4-1 UL 508 VDE 0660
Product Tradename	ZEB
Product Type	Electronic overload Relay
Product Sub Type	None
Catalog Notes	Rated operational current: Switch-on and switch-off conditions based on DC-13, time constant as specified.
Features & Functions	
Earth fault protection	None
Features	Phase-failure sensitivity (according to IEC/EN 60947, VDE 0660 Part 102)
Functions	Filament bulb (24 V)
General information	
Class	Adjustable
Degree of protection	IP20
Mounting method	Separate mounting Separate positioning
Overload release current setting - min	20 A
Overload release current setting - max	100 A
Overvoltage category	III
Pollution degree	3
Protection	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
Rated impulse withstand voltage (Uimp)	6000 V (auxiliary circuits) 6000 V AC
Shock resistance	Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Shock duration 10 ms
Suitable for	Branch circuits, (UL/CSA)
Voltage type	Self powered
Climatic environmental conditions	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	65 °C
Ambient operating temperature (enclosed) - max	45 °C
Climatic proofing	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Terminal capacities	

Terminal capacity (flexible with ferrule)		2 x (0.75 - 2.5) mm ² , Control circuit cables
Terminal capacity (solid)		2 x (0.75 - 4) mm ² , Control circuit cables 1 x (16 - 50) mm ² , Main cables
Terminal capacity (solid/stranded AWG)		1 x (6 - 1), Main cables 2 x (18 - 12), Control circuit cables
Stripping length (main cable)		14 mm
Stripping length (control circuit cable)		8 mm
Screw size		M3.5, Terminal screw, Control circuit cables
Screwdriver size		1 x 6 mm, Terminal screw, Control circuit cables, Standard screwdriver 2, Terminal screw, Control circuit cables, Pozidriv screwdriver
Tightening torque		0.8 - 1.2 Nm, Screw terminals, Control circuit cables 7 lb-in, Screw terminals
Electrical rating		
Conventional thermal current I_{th} of auxiliary contacts (1-pole, open)		5 A
Rated control supply voltage (Us) at AC, 50 Hz - min		0 V
Rated control supply voltage (Us) at AC, 50 Hz - max		0 V
Rated control supply voltage (Us) at AC, 60 Hz - min		0 V
Rated control supply voltage (Us) at AC, 60 Hz - max		0 V
Rated control supply voltage (Us) at DC - min		0 V
Rated control supply voltage (Us) at DC - max		0 V
Rated frequency - min		50 Hz
Rated frequency - max		60 Hz
Rated operational current (Ie) at AC-15, 120 V		1.5 A
Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V		1.5 A
Rated operational current (Ie) at AC-15, 380 V, 400 V, 415 V		0.9 A
Rated operational current (Ie) at DC-13, 110 V		0.4 A
Rated operational current (Ie) at DC-13, 220 V, 230 V		0.2 A
Rated operational current (Ie) at DC-13, 24 V		0.9 A
Rated operational current (Ie) at DC-13, 60 V		0.75 A
Rated operational voltage (Ue) at AC - max		690 V
Safe isolation		240 V AC, Between auxiliary contacts, According to EN 61140 440 V, Between auxiliary contacts and main contacts, According to EN 61140 600 V AC, Between main circuits, According to EN 61140
Short-circuit protection rating		Max. 6 A gG/gL, fuse, Without welding, Auxiliary and control circuits
Short-circuit current rating (high fault at 600 V)		100 kA, Fuse, SCCR (UL/CSA) 200 A, Class J, max. Fuse, SCCR (UL/CSA)
Switching capacity (auxiliary contacts, pilot duty)		R300, DC operated (UL/CSA) B600, AC operated (UL/CSA)
Voltage rating - max		600 V
Contacts		
Number of auxiliary contacts (change-over contacts)		0
Number of auxiliary contacts (normally closed contacts)		1
Number of auxiliary contacts (normally open contacts)		1
Number of contacts (normally closed contacts)		1
Number of contacts (normally open contacts)		1
Design verification		
Equipment heat dissipation, current-dependent P _{vid}		25.4 W
Heat dissipation capacity P _{diss}		0 W
Heat dissipation per pole, current-dependent P _{vid}		8.47 W
Rated operational current for specified heat dissipation (I _n)		100 A
Static heat dissipation, non-current-dependent P _{vs}		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Electronic overload relay (EC001080)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Overload protection device / Electronic overload relay (ecl@ss13-27-37-15-02 [AKF076019])		
Mounting method		Separate positioning
Type of electrical connection of main circuit		Screw connection
Adjustable current range	A	20 - 100
External power supply required		No
Rated control supply voltage AC 50 Hz	V	0 - 0
Rated control supply voltage AC 60 Hz	V	0 - 0
Rated control supply voltage DC	V	0 - 0
Voltage type for actuating		
Number of auxiliary contacts as normally closed contact		1
Number of auxiliary contacts as normally open contact		1
Number of auxiliary contacts as change-over contact		0
Voltage type (operating voltage)		AC
Operating voltage AC 50 Hz	V	230 - 690
Operating voltage AC 60 Hz	V	230 - 690
Operating voltage DC	V	0 - 0
Rated switch current	A	
Release class		Adjustable
Reset function automatic		Yes
Reset function input		No
Reset function push-button		Yes
Width	mm	56
Height	mm	120
Depth	mm	140.5