

ECO gateway for XI/ON I/O system, integrated



Part no. XNE-GWBR-CANOPEN
140044
EL Number 4520000
(Norway)

General specifications	
Product name	Eaton XNE Gateway
Part no.	XNE-GWBR-CANOPEN
EAN	7640130120600
Product Length/Depth	129 millimetre
Product height	75 millimetre
Product width	33.5 millimetre
Product weight	0.136 kilogram
Certifications	Rated data for terminations according to IEC/EN 60947-7-1 CULus IEC/EN 61000-6-2 IEC/EN 61000-6-4 CE IEC/EN 61131-2 IEC/EN 6113-2
Product Tradename	XNE
Product Type	Gateway
Product Sub Type	None
Catalog Notes	supports up to 62 disc-type modules (XN, XNE)
Features & Functions	
Features	Fieldbus connection over separate bus coupler possible
Fitted with:	Bus refreshing module Potential separation
General information	
Accessories	1 x end plate XN-ABPL and 2 x end bracket XN-WEW-32/2-SW included with supplied equipment.
Admissible range	18 - 30 V DC, Networking
Configuration	Maximum station configuration: 62 cards (XN, XNE) of slice design or max. length of station: 1 m
Degree of protection	IP20
Mounting method	Rail mounting possible
Residual ripple	According to EN 61131-2
Type	XI/ON ECO gateways XNE-Gateway with integrated supply
Voltage type	DC
Ambient conditions, mechanical	
Drop and topple	According to IEC 60068-2-31, free fall according to IEC 60068-2-32
Shock resistance	Mechanical, According to IEC/EN 60068-2-27 Continuous according to IEC/EN 60068-2-29
Vibration resistance	According to IEC/EN 60068-2-6
Climatic environmental conditions	
Ambient operating temperature - min	0 °C
Ambient operating temperature - max	55 °C
Ambient storage temperature - min	-25 °C
Ambient storage temperature - max	85 °C
Environmental conditions	Harmful gasses - H2S: 1 ppm (relative humidity < 75%, no condensation) Harmful gasses - SO2: 10 ppm (relative humidity < 75%, no condensation)
Relative humidity	5 - 95 % (indoor, Level RH-2, non-condensing for storage at 45°C)
Electro magnetic compatibility	
Air discharge	According to EN 61100-4-2
Burst impulse	According to IEC/EN 61000-4-4
Contact discharge	According to EN 61100-4-2

Electromagnetic fields		According to IEC EN 61100-4-2
Emitted interference		230 - 1000 MHz (radiated, high frequency, according to EN 55016-2-3) 30 - 230 MHz (radiated, high frequency, according to EN 55016-2-3)
Radiated RFI		IEC/EN 61100-4-6
Surge rating		According to IEC/EN 61000-4-5 Level 4
Voltage dips		According to EN 61131-2 (Voltage fluctuations/voltage dips)
Terminal capacities		
Terminal capacity		0.25 - 1.5 mm ² , with ferrules without plastic collar 0.25 - 1.5 mm ² , solid 0.25 - 1.5 mm ² , flexible without ferrule 0.25 - 0.75 mm ² , with ferrules with plastic collar
Gauge pin		A1 (according to IEC/EN 60947-1)
Stripping length (main cable)		8 mm
Electrical rating		
Supply voltage		4.7 - 5.3 V DC
Supply voltage at AC, 50 Hz - min		0 V
Supply voltage at AC, 50 Hz - max		0 V
Supply voltage at DC - min		18 V
Supply voltage at DC - max		30 V
Communication		
Addressing		Address set via DIP switch Address range: 1 - 63 decimal
Bus termination		Via DIP switch, Networking
Connection type		Push-In spring-cage terminals, Field bus Spring-cage terminals, Field bus/Supply voltage) Push-In spring-cage terminals, Connection design in TOP direction
Data transfer rate		800 kBit/s 50 kBit/s 500 kBit/s, Networking 800 kBit/s, Networking 125 kBit/s, Networking 250 kBit/s 10 kBit/s, Networking 1000 kBit/s, Networking 1000 kBit/s 20 kBit/s Setting through DIP switch or automatically 50 kBit/s, Networking 250 kBit/s, Networking 500 kBit/s 125 kBit/s
Field voltage		24 V DC (UL)
Interfaces		PS/2 socket (Service interface) CANopen®, Field bus connection
Protocol		CANopen® CAN Other bus systems
Safety		
Explosion safety category for dust		None
Explosion safety category for gas		None
Potential isolation		Through optocoupler: yes
Design verification		
Equipment heat dissipation, current-dependent P _{vid}		0 W
Heat dissipation capacity P _{diss}		0 W
Heat dissipation per pole, current-dependent P _{vid}		0 W
Rated operational current for specified heat dissipation (I _n)		0 A
Static heat dissipation, non-current-dependent P _{vs}		6 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Meets the product standard's requirements.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Programmable logic controllers PLC (EG000024) / Fieldbus, decentr. periphery - communication module (EC001604)		
Electric engineering, automation, process control engineering / Control, Process Control System (PCS) / Field bus, decentralized peripheral / Field bus, decentralized peripheral - communications module (ecl@ss13-27-24-26-08 [BAA073018])		
Supply voltage AC 50 Hz	V	0 - 0
Supply voltage AC 60 Hz	V	0 - 0
Supply voltage DC	V	18 - 30
Voltage type (supply voltage)		DC
Number of HW-interfaces CAN		
Number of HW-interfaces industrial Ethernet		
Number of interfaces PROFINET		
Number of HW-interfaces RS-232		
Number of HW-interfaces RS-422		
Number of HW-interfaces RS-485		
Number of HW-interfaces serial TTY		
Number of HW-interfaces USB		
Number of HW-interfaces parallel		
Number of HW-interfaces wireless		
Number of HW-interfaces other		
Supporting protocol for EtherCAT		No
Supporting protocol for TCP/IP		No
Supporting protocol for PROFIBUS		No
Supporting protocol for CAN		Yes
Supporting protocol for INTERBUS		No
Supporting protocol for ASI		No
Supporting protocol for KNX		No
Supporting protocol for Modbus		No
Supporting protocol for Data-Highway		No
Supporting protocol for DeviceNet		No
Supporting protocol for SUCONET		No
Supporting protocol for LON		No
Supporting protocol for SERCOS		No
Supporting protocol for PROFINET IO		No
Supporting protocol for PROFINET CBA		No
Supporting protocol for Foundation Fieldbus		No
Supporting protocol for EtherNet/IP		No
Supporting protocol for AS-Interface Safety at Work		No
Supporting protocol for DeviceNet Safety		No
Supporting protocol for INTERBUS-Safety		No

Supporting protocol for PROFIsafe			No
Supporting protocol for SafetyBUS p			No
Supporting protocol for other bus systems			Yes
Radio standard Bluetooth			No
Radio standard WLAN 802.11			No
Radio standard GPRS			No
Radio standard eGPRS			No
Radio standard GSM			No
Radio standard LTE			No
Radio standard UMTS			No
IO link master			No
System accessory			Yes
Degree of protection (IP)			IP20
With potential separation			Yes
Fieldbus connection over separate bus coupler possible			Yes
Rail mounting possible			Yes
Wall mounting/direct mounting			No
Front built-in possible			No
Rack-assembly possible			No
Suitable for safety functions			No
SIL according to IEC 61508			None
Performance level according to EN ISO 13849-1			None
Appendant operation agent (Ex ia)			No
Appendant operation agent (Ex ib)			No
Explosion safety category for gas			None
Explosion safety category for dust			None
Certified for UL hazardous location class I			No
Certified for UL hazardous location class II			No
Certified for UL hazardous location class III			No
Certified for UL hazardous location division 1			No
Certified for UL hazardous location division 2			No
Certified for UL hazardous location group A (acetylene)			No
Certified for UL hazardous location group B (hydrogen)			No
Certified for UL hazardous location group C (ethylene)			No
Certified for UL hazardous location group D (propane)			No
Certified for UL hazardous location group E (metal dusts)			No
Certified for UL hazardous location group F (carbonaceous dusts)			No
Certified for UL hazardous location group G (non-conductive dusts)			No
Width		mm	33.5
Height		mm	75
Depth		mm	129