

Lightning current and surge arresters kit, TN-S kit, 2p



Part no. SPBT12-280/2
158309
EL Number 1609776
(Norway)

General specifications		
Product name		Eaton Moeller series xPole - SPBT12 Surge Protection Device
Part no.		SPBT12-280/2
EAN		4015081548873
Product Length/Depth		86 millimetre
Product height		69 millimetre
Product width		35 millimetre
Product weight		0.285 kilogram
Compliances		RoHS conform
Product Tradename		xPole - SPBT12
Product Type		Surge Protection Device
Product Sub Type		None
Delivery program		
Application		Open areas Residential buildings Utility buildings
Number of poles		Two-pole
Type		Surge arrester
Technical Data - Electrical		
Voltage protection level		1.5 kV
Voltage protection level (DC+ - DC-)		0 kV
Voltage protection level (DC+/DC- - PE)		0 kV
Voltage protection level (L-N)		0 kV
Voltage protection level (L-PE)		1.5 kV
Voltage protection level (N-PE)		0 kV
Nominal voltage at AC		280 V
Nominal voltage at DC		0 V
Continuous voltage at AC - max		280 V
Continuous voltage at DC - max		0 V
PV-voltage - max		0 V
Lightning impulse current (10/350 µs)		12.5 kA
Follow current extinguishing capability		0 kA
Signalling at the device		Optic
Specific energy (W/R)		39.1 kJ/Ohm
Technical Data - Mechanical		
Frame		2 modular spacing
Mounting method		DIN rail (top hat rail) 35 mm
Conductor cross section (flexible, fine-strand) - max		35 mm ²
Conductor cross section (solid, solid-strand) - max		25 mm ²
Degree of protection		IP20
Additional information		
System configuration type		TN Other TN-S TT
Test class		Type 1 + 2

Technical data ETIM 9.0

Earthing, lightning and surge protection (EG000021) / Combined arrester for power supply systems (EC001457)

System configuration DC			No
System configuration IT			No
System configuration TN			Yes
System configuration TN-C			No
System configuration TN-C-S			No
System configuration TN-S			Yes
System configuration TT			Yes
System configuration other			Yes
Number of poles			2
Lightning impulse current (10/350 µs)		kA	12.5
Max. continuous voltage AC		V	280
Max. continuous voltage DC		V	0
Nominal voltage AC		V	280
Nominal voltage DC		V	0
Max. PV-voltage		V	0
Voltage protection level		kV	1.5
Voltage protection level L-N		kV	0
Voltage protection level L-PE		kV	1.5
Voltage protection level N-PE		kV	0
Voltage protection level (DC+ - DC-)		kV	0
Voltage protection level (DC+/DC- - PE)		kV	0
Follow current extinguishing capability		kA	0
Specific energy (W/R)		kJ/Ohm	39.1
Max. overcurrent protection device, parallel connection (fuse)		A	0
Max. overcurrent protection device, series connection (fuse)		A	160
Mounting method			DIN rail (top hat rail) 35 mm
Construction size			2 modular spacing
Max. conductor cross section solid (solid, stranded)		mm ²	25
Max. conductor cross section flexible (fine-strand)		mm ²	35
Remote signalling			No
Signalling at the device			Optical
Test class			Type 1 + 2
Integrated backup fuse			No
Energy-coordinated protection effect with regard to the terminal equipment			No
Voltage switching spark gap technology			No
Overcurrent protected voltage tapping			No
Degree of protection (IP)			IP20