





Flashing light module; red; LED;120 V

Part no. **SL4-BL120-R**  
 Catalog No. **171345**  
 Alternate Catalog No. **SL4-BL120-R**  
 EL-Nummer (Norway) **4137580**

### Delivery program

|                            |       |   |   |
|----------------------------|-------|---|---|
| Product range              |       |   | SL signal towers  |
| Basic function             |       |   | Flashing light module   |
| Degree of Protection       |       |   | IP66  |
| Rated operational voltage  | $U_e$ | V | 110/120 V AC  |
| Type of light              |       |   | Flashing light  |
| Light elements             |       |   | LED   |
| <b>Colour</b>              |       |   |   |
|                            |       |   | Red   |
|                            |       |   |   |
| Function                   |       |   |  |
| Connection to SmartWire-DT |       |   | no  |

### Technical data

#### General

|                             |  |    |   |
|-----------------------------|--|----|---|
| Standards                   |  |    | IEC/EN 60947-5-1  |
| Climatic proofing           |  |    | Damp heat, cyclic, to IEC 60068-2-30                                      |
| Mounting position           |  |    | As required   |
| Mechanical shock resistance |  | g  | > 15<br>according to IEC 60068-2-27<br>Shock duration 11 ms<br>Sinusoidal |
| IEC degree of protection    |  |    | IP66<br>IEC/EN 60529  |
| Protection type UL          |  |    | Type 4, 4X, 13  |
| Material                    |  |    | Enclosure: Polycarbonate (PC), black<br>Cap: Polycarbonate (PC)           |
| Cap colour                  |  |    | Red   |
| Ambient temperature         |  | °C | -30 - +60   |
| Number of signal elements   |  |    | Max. 5 with standard base<br>Max. 10 with base for mounting on both sides |
| Weight                      |  | g  | 45  |

#### Contacts

|                                       |           |      |       |
|---------------------------------------|-----------|------|-------|
| Rated impulse withstand voltage       | $U_{imp}$ | V AC | 4000  |
| Rated insulation voltage              | $U_i$     | V    | 250   |
| Overtoltage category/pollution degree |           |      | III/3 |

#### modules

|                           |  |   |                |
|---------------------------|--|---|----------------|
| Type of light             |  |   | Flashing light |
| Light elements            |  |   | LED            |
| Flashing/strobe frequency |  |   | 2 Hz           |
| Leakage current           |  | A | < 0.003        |
| lifespan                  |  | h | > 100000       |

|                            |  |   |                     |
|----------------------------|--|---|---------------------|
| Transmission angle         |  |   | 360°                |
| Current-/power consumption |  |   |                     |
| at 110/120 V AC            |  | A | 0.030               |
| Voltage range              |  |   | 110/120 V AC ± 10 % |

## Design verification as per IEC/EN 61439

|  |  |    |     |
|--|--|----|-----|
| Technical data for design verification |  |    |     |
| Operating ambient temperature min.     |  | °C | -30 |
| Operating ambient temperature max.     |  | °C | 60  |

## Technical data ETIM 7.0

|   |  |    |               |
|---|--|----|---------------|
| Low-voltage industrial components (EG000017) / Optical module for signal tower (EC000232)   |  |    |               |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Optical module for signal tower (ecl@ss10.0.1-27-37-12-20 [AKF038014]) |  |    |               |
| Function  |  |    | Blinker light |
| Colour  |  |    | Red           |
| Outer diameter  |  | mm | 43            |
| Operating voltage at AC 50 Hz   |  | V  | 110 - 120     |
| Operating voltage at AC 60 Hz   |  | V  | 110 - 120     |
| Operating voltage at DC   |  | V  | 0 - 0         |
| Voltage type  |  |    | AC            |
| Lamp type   |  |    | LED           |
| Colour housing  |  |    | Black         |
| Degree of protection (IP)   |  |    | IP66          |
| Degree of protection (NEMA)   |  |    | 4X            |

## Approvals

|                             |  |  |  |
|-----------------------------|--|--|--|
| Product Standards           |  |  | IEC/EN 60947-5-1; UL 508; CSA-C22.2 No. 14-10; CSA-C22.2 No. 94-91; CE marking |
| UL File No.                 |  |  | E29184   |
| UL Category Control No.     |  |  | NKCR   |
| CSA File No.                |  |  | UL report applies to both US and Canada  |
| CSA Class No.               |  |  | NKCR7  |
| North America Certification |  |  | UL listed, certified by UL for use in Canada                                   |
| Degree of Protection        |  |  | UL Type 4, 4X, 13  |

## Dimensions



## Assets (links)

### Declaration of CE Conformity

00002899

### Instruction Leaflets

IL047001ZU2018\_05

## Additional product information (links)

### IL047001ZU SL4 Main Instruction

IL047001ZU SL4 Main Instruction

[ftp://ftp.moeller.net/DOCUMENTATION/AWA\\_INSTRUCTIONS/IL047001ZU2018\\_05.pdf](ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL047001ZU2018_05.pdf)