

Acoustic module;230 V;continuous or pulsed tone

Part no. SL4-AP230
171381
EL Number 4137616
(Norway)

| General specifications | | |
|--|--|--|
| Product name | | Eaton Moeller® series SL4 Acoustic module |
| Part no. | | SL4-AP230 |
| EAN | | 4015081679102 |
| Product Length/Depth | | 43 millimetre |
| Product height | | 72 millimetre |
| Product width | | 43 millimetre |
| Product weight | | 0.046 kilogram |
| Certifications | | CE IEC/EN 60529 CSA Class No.: NKCR7 Certified by UL for use in Canada UL report applies to both US and Canada IEC/EN 60947-5-1 CSA-C22.2 No. 14-10 UL UL Category Control No.: NKCR UL 508 CSA-C22.2 No. 94-91 UL File No.: E29184 |
| Product Tradename | | SL4 |
| Product Type | | Acoustic module |
| Product Sub Type | | None |
| Features & Functions | | |
| Color | | Black |
| Functions | | Continuous tone/pulse tone |
| General information | | |
| Alarm type | | Internal sound setting, 1 pole DIP Tone adjustable 2 types of sound Pulsed tone Continuous tone |
| Connection to SmartWire-DT | | No |
| Current consumption | | 0.021 A, at 230/240 V AC |
| Degree of protection | | NEMA 13 IP66 |
| Frequency rating | | 4000 Hz |
| Loudness | | 80 dB |
| Material | | Cap: Polycarbonate (PC) Enclosure: Polycarbonate (PC) |
| Mounting position | | As required Place only at the highest position on a pole |
| Overvoltage category | | III |
| Pollution degree | | 3 |
| Product Category | | SL signal towers |
| Radiation angle | | 360 ° |
| Rated impulse withstand voltage (Uimp) | | 4000 V AC |
| Shock resistance | | Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms |
| Type | | Acoustic module |
| Voltage type | | AC |
| Climatic environmental conditions | | |
| Ambient operating temperature - min | | -30 °C |
| Ambient operating temperature - max | | 60 °C |
| Climatic proofing | | Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30 |

| Electrical rating | | |
|--|--|---------|
| Leakage current | | 0.003 A |
| Rated insulation voltage (Ui) | | 250 V |
| Rated operational current (Ie) - max | | 21 A |
| Rated operational voltage (Ue) at AC - min | | 230 V |
| Rated operational voltage (Ue) at AC - max | | 240 V |
| Rated operational voltage (Ue) at DC - min | | 0 V |
| Rated operational voltage (Ue) at DC - max | | 0 V |

Technical data ETIM 9.0

| Low-voltage industrial components (EG000017) / Acoustic module for signal tower (EC001261) | | |
|---|----|----------------------------|
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Signal column element, acoustic (ecl@ss13-27-37-12-37 [AKF055019]) | | |
| Function | | Continuous tone/pulse tone |
| Outer diameter | mm | 43 |
| Colour | | Black |
| Operating voltage AC 50 Hz | V | 230 - 240 |
| Operating voltage AC 60 Hz | V | 230 - 240 |
| Operating voltage DC | V | 0 - 0 |
| Voltage type | | AC |
| Tone adjustable | | Yes |
| Degree of protection (IP) | | IP66 |
| Degree of protection (NEMA) | | 13 |
| Loudness | dB | 80 |