

Base module;external fixing holes

Part no. SL7-CB-EMH
171449
EL Number 4137704
(Norway)

| General specifications | | |
|--|--|--|
| Product name | | Eaton Moeller® series SL7 Base module |
| Part no. | | SL7-CB-EMH |
| EAN | | 4015081677795 |
| Product Length/Depth | | 100 millimetre |
| Product height | | 94 millimetre |
| Product width | | 100 millimetre |
| Product weight | | 0.176 kilogram |
| Certifications | | UL 508 Certified by UL for use in Canada IEC/EN 60529 CSA Class No.: NKCR7 CE IEC/EN 60947-5-1 UL report applies to both US and Canada UL CSA-C22.2 No. 94-91 UL File No.: E29184 CSA-C22.2 No. 14-10 UL Category Control No.: NKCR |
| Product Tradename | | SL7 |
| Product Type | | Base module |
| Product Sub Type | | None |
| Features & Functions | | |
| Color | | Other |
| Fitted with: | | Cover External fixing holes |
| Number of modules | | Max. 10 (with base for mounting on both sides) Max. 5 Max. 5 (with standard base) |
| General information | | |
| Connection to SmartWire-DT | | No |
| Degree of protection | | IP66 NEMA 4X NEMA 13 NEMA 4 |
| Mounting Method | | Bracket Horizontal Floor |
| Mounting position | | As required |
| Overvoltage category | | III |
| Pollution degree | | 3 |
| Product Category | | SL signal towers |
| Rated impulse withstand voltage (Uimp) | | 4000 V AC |
| Shock resistance | | Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms |
| Type | | Base module |
| Climatic environmental conditions | | |
| Ambient operating temperature - min | | -30 °C |
| Ambient operating temperature - max | | 60 °C |
| Climatic proofing | | Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78 |
| Terminal capacities | | |
| Terminal capacity (AWG) | | 24 - 14 |
| Terminal capacity (flexible with ferrule and plastic collar) | | 0.25 - 1.5 mm ² |
| Terminal capacity (solid/flexible) | | 0.13 - 2.5 mm ² |

| Electrical rating | | |
|-------------------------------|--|---|
| Rated insulation voltage (Ui) | | 250 V |
| Rated operational voltage | | 230/240 V AC ± 10 % 24 V AC/DC ± 10 % 110/120 V AC ± 10 % |

Technical data ETIM 9.0

| | | |
|--|--|-------------------------|
| Low-voltage industrial components (EG000017) / Connection module for signal tower (EC001152) | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Signal column element, connection module (ecI@ss13-27-37-12-32 [AKF050019]) | | |
| Connection type auxiliary circuit | | Spring clamp connection |
| Suitable for tube mounting | | No |
| Suitable for angle mounting | | Yes |
| Suitable for floor mounting | | Yes |
| Colour | | Other |
| Suitable for AS interface | | No |
| Suitable for M12 connector | | No |
| Suitable for IO link | | No |