Handle, black, lockable, for metal shaft, for padlock, for P3



Part no. SVB-SW-P3/M 172843

General specifications	
Product name	Eaton Moeller® series SVB Accessory Handle
Part no.	SVB-SW-P3/M
EAN	4015081694259
Product Length/Depth	88 millimetre
Product height	88 millimetre
Product width	88 millimetre
Product weight	0.13 kilogram
Compliances	CE
Product Tradename	SVB
Product Type	Accessory
Product Sub Type	Handle
Features & Functions	
Color	Black
Features	Lockable
Fitted with:	Padlocking feature
Locking facility	Lockable with a maximum of 3 padlocks
Locking mechanism	Lockable in the 0 (Off) position (interlock)
General information	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	50 °C
Degree of protection	NEMA Other
Suitable for	Switch disconnector Only for main switch
Switching angle	90 °
Туре	Assembly kit Main switch assembly kit With black rotary handle and black locking ring
Design verification	
Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdiss	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	0 A
Static heat dissipation, non-current-dependent Pvs	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	Not applicable.
10.11 Short-circuit rating	Not applicable.
10.12 Electromagnetic compatibility	Not applicable.
10.13 Mechanical function	Not applicable.

Technical data ETIM 9.0

Tooliiloul data Ellin 6.5		
Low-voltage industrial components (EG000017) / Handle for power circuit breaker (EC000229)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Handle for switch devices (ecl@ss13-27-37-04-14 [AKF012019])		
With restart blockage	No	
With key lock	No	
Padlock locking	No	
Colour	Black	
Suitable for emergency stop	No	
With extension shaft	No	
Suitable for power circuit breaker	No	
Suitable for switch disconnector	Yes	
Degree of protection (NEMA)	Other	