



Hollow wall wall trough 4-row; form of delivery for projects

Part no. **KLV-HW4-4PR**
 Catalog No. **178845**

Delivery program

Product image			
Basic function			Basic device
Product function			Installation distribution boards
Product range			KLV for projects
Design			Hollow wall
Installation site			Indoor
Type of installation			Hollow-wall mounting
Door/Flap			White
Degree of Protection			IP30
Colour			White
Shroud for protection against accidental contact			Plastic
Rows	Count		4
Module units per row			12
Description			IP30 Protection Class II Plastic housing
Cable entries			Cable entries on top and bottom, side, back plate
Equipment supplied			Empty wall trough Spirit level Device support rails Guard Installation instructions

Technical data

General

Standards			IEC/EN 62208, IEC/EN 60670-24
RoHS (in accordance with Directive 2002/95/EC of the European Parliament and Council)			conform
Ambient temperature		°C	-5 - +40
Degree of Protection			IP30
Protection class			II (totally insulated)
Rated frequency	f	Hz	50

Material characteristics

Material			Polystyren (plastic)
Colour			white (RAL 9016)

Material properties

Mechanical			
Impact resistance			IK05

Technical data ETIM 7.0

Distribution boards (EG000023) / Accessories for small distribution board (EC002287)
Electric engineering, automation, process control engineering / Electrical installation, device / Electrical distribution system (incl. small distribution board) / Electrical distribution system (incl. small distribution board, accessories) (ec1@ss10.0.1-27-14-24-92 [AFR782003])

Type of accessory		Other
-------------------	--	-------

Additional product information (links)

IL014007Z KLV compact distribution board	
IL014007Z KLV compact distribution board	ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL014007ZU2015_10.pdf
Product overview (Web)	http://www.eaton.eu/DE/Europe/Electrical/ProductsServices/Residential/index.htm