



**Combination plug-in terminal KSK; individual; green for neutral conductor**

**Part no. KSK-PE**  
**Catalog No. 178904**

### Delivery program

Basic function		Accessory consideration
Accessories		General
Product range		KLV DBO
Degree of Protection		IP2X

### Technical data ETIM 7.0

Terminal blocks (EG000012) / Single- and multi-pole terminal strip (EC001284)		
Electric engineering, automation, process control engineering / Electrical installation, device / Terminal (not overhead line) / Single- and multi-pole terminal strip (ecl@ss10.0.1-27-14-11-06 [AAB921016])		
Drill hole distance centrally	mm	1
Explosion-tested version 'Ex e'		No
Connectable conductor cross section fine-strand without cable end sleeve	mm <sup>2</sup>	2.5 - 25
Connectable conductor cross section fine-strand with cable end sleeve	mm <sup>2</sup>	2.5 - 16
Connectable conductor cross section solid-core	mm <sup>2</sup>	2.5 - 25
Connectable conductor cross section multi-wired	mm <sup>2</sup>	2.5 - 25
Rated current I <sub>n</sub>	A	63
Rated voltage	V	400
Type of electrical connection 1		Screw connection
Type of electrical connection 2		Plug-in connection
Connection position		Inclined
Number of poles		1
Number of clamp positions per pole		8
Mounting method		Direct mounting
Material insulation body		Thermoplastic
Operation temperature	°C	35 - 35
Inflammability class of insulation material acc. with UL94		V0
Width/grid dimension	mm	55
Height at lowest possible mounting height	mm	17
Length	mm	19.5
Closing plate required		No
Colour		Green
Transparent		No

### Additional product information (links)

Product overview (Web)	<a href="http://www.eaton.eu/DE/Europe/Electrical/ProductsServices/Residential/index.htm">http://www.eaton.eu/DE/Europe/Electrical/ProductsServices/Residential/index.htm</a>
------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------