



LED, white, BA15d, 24VAC/DC

**Part no.** SL-LED-W  
**Catalog No.** 215278  
**Alternate Catalog No.** SL-LED-W

### Delivery program

Product range			SL signal towers
Single unit/Complete unit			Stand-alone device
			Socket size BA-15d
Lifespan to EN 60064 at $t_a = +25\text{ }^\circ\text{C}$	$t_{\text{mean}}$ (AC)	h	100000
Rated operational voltage	$U_e$	V	18 - 30 V AC 50/60 Hz 18 - 30 V DC
Rated operational current	$I_e$	mA	13 - 50
<b>Colour</b>			
			White
Connection to SmartWire-DT			no

### Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		$^\circ\text{C}$	-25
Operating ambient temperature max.		$^\circ\text{C}$	55

### Technical data ETIM 5.0

Lamps (EG000028) / Indication- and signalling lamp (EC000399)			
Electric engineering, automation, process control engineering / Lighting installation, device / Light medium / Indication- and signal lamp (ecl@ss8-27-11-06-31 [AKE242010])			
Lamp voltage		V	24 - 30
Luminous flux		lm	0
Socket			BA15d
Lamp			LED
Lamp shape			-
Halogen			No
Krypton			No
Xenon			No
Colour			White
Colour temperature		K	0
Diameter		mm	0
Total length		mm	42
Suitable for torches			No
Suitable for pointer			Yes
Nominal current		mA	50
Lamp power		W	1,5
Average nominal lifespan		h	100000

### Approvals

Product Standards			IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94-91; CE marking
UL File No.			E29184
UL Category Control No.			NKCR

CSA File No.		012528
CSA Class No.		3211-03
North America Certification		UL listed, CSA certified

## Additional product information (links)

### IL04716024Z (AWA1160-1685) Pillar lamps

IL04716024Z (AWA1160-1685) Pillar lamps [https://es-assets.eaton.com/DOCUMENTATION/AWA\\_INSTRUCTIONS/IL04716024Z2018\\_05.pdf](https://es-assets.eaton.com/DOCUMENTATION/AWA_INSTRUCTIONS/IL04716024Z2018_05.pdf)