Neutral terminal

Part no. K-CI-K5 218488



General specifications		
Product name	Eaton Moeller® series K-CI Accessory Neutral terminal	
Part no.	K-CI-K5	
EAN	4015082184889	
Product Length/Depth	36 millimetre	
Product height	60 millimetre	
Product width	18 millimetre	
Product weight	0.05 kilogram	
Certifications	UL/CSA certification not required	
Product Tradename	K-CI	
Product Type	Accessory	
Product Sub Type	Neutral terminal	
Features & Functions		
Fitted with:	PE, N adhesive labels	
Functions	For snap-fitting onto mounting rail	
	Connection of a 5th conductor	
General information		
Accessory/spare part type	Connector	
Product category	CI-K small enclosures	
Туре	Neutral terminals	
Used with	T5/I5, T5/I5	
Climatic environmental conditions		
Ambient operating temperature - min	-25 °C	
Ambient operating temperature - max	40 °C	
Terminal capacities		
Terminal capacity	Round solid copper conductor, 2.5 - 50 mm ² 2 x 50 mm ² Cu ribbon cable, 3 x 9 x 0.8 mm Round stranded copper conductor, 2.5 - 50 mm ² Round flexible copper conductor with ferrule, 2.5 - 35 mm ²	
Stripping length (main cable)	16 mm	
Screw size	5 mm AF, Hexagon socket-head spanner	
Electrical rating		
Rated operational voltage	690 V	
Rated uninterrupted current (Iu)	150 A	
Design verification		
Equipment heat dissipation, current-dependent Pvid	0 W	
Heat dissipation capacity Pdiss	0 W	
Heat dissipation per pole, current-dependent Pvid	7.5 W	
Rated operational current for specified heat dissipation (In)	100 A	
Static heat dissipation, non-current-dependent Pvs	0 W	
10.2.2 Corrosion resistance	Meets the product standard's requirements.	
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.	
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.	
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.	
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.	
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.	
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.	
10.2.7 Inscriptions	Meets the product standard's requirements.	

10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility. The specifications for the switchgear must b observed.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Accessories/spare parts for low-voltage switch technology (EC002498)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology (accessories) (ecl@ss13-27-37-13-92 [AKN570018])

Type of accessory/spare part	Connector	
Accessory	Yes	
Spare part	No	