



**Replacement coil, Tool-less plug connection, TVC200: 200 V 50 Hz, 200 - 220 V 60 Hz, AC, For use with: DILM80, DILM100**

**Part no. DILM95-XSP(TVC200)**  
**Catalog No. 230077**  
**Alternate Catalog No. XTCERENCOILFDH**

## Delivery program

Connection technique			Tool-less plug connection
Actuating voltage			TVC200: 200 V 50 Hz, 200 - 220 V 60 Hz
Voltage AC/DC			AC
For use with			DILM80 DILM100

## Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Coil for relay (EC001043)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Reel for contactor (ecl@ss10.0.1-27-37-10-12 [AKF021013])			
Rated control supply voltage Us at AC 50HZ		V	200 - 200
Rated control supply voltage Us at AC 60HZ		V	200 - 220
Rated control supply voltage Us at DC		V	0 - 0
Voltage type for actuating			AC

## Assets (links)

### Instruction Leaflets

IL03407042Z2018\_05

## Additional product information (links)

<b>IL03407042Z (AWA2100-2290) Coil change: DILM80...DILM170</b>	
IL03407042Z (AWA2100-2290) Coil change: DILM80...DILM170	<a href="ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL03407042Z2018_05.pdf">ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL03407042Z2018_05.pdf</a>
Motor starters and "Special Purpose Ratings" for the North American market	<a href="http://www.eaton.eu/ecm/groups/public/@pub/@europe/@electrical/documents/content/pct_3258146.pdf">http://www.eaton.eu/ecm/groups/public/@pub/@europe/@electrical/documents/content/pct_3258146.pdf</a>
Switchgear of Power Factor Correction Systems	<a href="http://www.moeller.net/binary/ver_techpapers/ver934en.pdf">http://www.moeller.net/binary/ver_techpapers/ver934en.pdf</a>
X-Start - Modern Switching Installations Efficiently Fitted and Wired Securely	<a href="http://www.moeller.net/binary/ver_techpapers/ver938en.pdf">http://www.moeller.net/binary/ver_techpapers/ver938en.pdf</a>
Mirror Contacts for Highly-Reliable Information Relating to Safety-Related Control Functions	<a href="http://www.moeller.net/binary/ver_techpapers/ver944en.pdf">http://www.moeller.net/binary/ver_techpapers/ver944en.pdf</a>
Effect of the Cable Capacitance of Long Control Cables on the Actuation of Contactors	<a href="http://www.moeller.net/binary/ver_techpapers/ver949en.pdf">http://www.moeller.net/binary/ver_techpapers/ver949en.pdf</a>
Switchgear for Luminaires	<a href="http://www.moeller.net/binary/ver_techpapers/ver955en.pdf">http://www.moeller.net/binary/ver_techpapers/ver955en.pdf</a>
Standard Compliant and Functionally Safe Engineering Design with Mechanical Auxiliary Contacts	<a href="http://www.moeller.net/binary/ver_techpapers/ver956en.pdf">http://www.moeller.net/binary/ver_techpapers/ver956en.pdf</a>
The Interaction of Contactors with PLCs	<a href="http://www.moeller.net/binary/ver_techpapers/ver957en.pdf">http://www.moeller.net/binary/ver_techpapers/ver957en.pdf</a>
Busbar Component Adapters for modern Industrial control panels	<a href="http://www.moeller.net/binary/ver_techpapers/ver960en.pdf">http://www.moeller.net/binary/ver_techpapers/ver960en.pdf</a>