



Two way switch 22 CO, 16A, 230 V, 20kA

Part no. Z-S/2WTN
Catalog No. 248348

Similar to illustration

Design verification as per IEC/EN 61439

| | | | |
|--|----------------|---|----|
| Technical data for design verification | | | |
| Rated operational current for specified heat dissipation | I _n | A | 20 |

Technical data ETIM 7.0

| | | | |
|--|--|----|----------------|
| Devices for distribution board-/surface mounting (EG000062) / Main switch for distribution board (EC001545) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Main switch for distribution board (ecI@ss10.0.1-27-14-23-01 [AFZ813014]) | | | |
| Switching function | | | Two-way switch |
| Number of contacts as normally open contact | | | 0 |
| Number of contacts as normally closed contact | | | 0 |
| Number of contacts as change-over contact | | | 2 |
| Number of poles | | | 0 |
| Rated current | | A | 16 |
| Rated voltage | | V | 230 |
| Min. rated voltage | | V | 0 |
| Rated switching capacity | | kA | 20 |
| Short-circuit breaking capacity (I _{cw}) | | kA | 10 |
| Voltage type | | | AC |
| Forced segregation (according to DIN VDE 0113) | | | No |
| With signal lamp | | | No |
| Colour calotte | | | Other |
| Lamp type | | | Other |
| Lamp socket | | | Other |
| Max. lamp power | | W | 0 |
| Width in number of modular spacings | | | 2 |
| Built-in depth | | mm | 80 |
| Degree of protection (IP) | | | IP40 |