

Auxiliary contact, for PLHT/AZ, 1N/O+1N/C, 0.5HP

Part no. **Z-LHK**
 248440
EL Number **1609565**
(Norway)

General specifications

Product name	Eaton Distribution parts
Part no.	Z-LHK
EAN	4015082484408
Product Length/Depth	80 millimetre
Product height	75 millimetre
Product width	8.8 millimetre
Product weight	0.041 kilogram
Compliances	RoHS conform
Certifications	EN45545-2 IEC 61373
Product Tradename	None
Product Type	Distribution parts
Product Sub Type	None
Public Consumption	Yes
Product Family Description	ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable	Yes

Product Specification Details

Accessory/spare part type	Auxiliary contacts
Additional equipment required	Auxiliary switch
Ambient operating temperature - max	40 °C
Ambient operating temperature - min	-5 °C
Application	Switchgear for industrial and advanced commercial applications
Assembly width	0.5
Device fitting	Universal
EL number	1609565
Functions	Auxiliary switch
Number of contacts (change-over contacts)	0
Number of contacts (normally closed contacts)	1
Number of contacts (normally open contacts)	1
Number of poles at main contact unit - max	2
Number of switches (fault signal)	0
Rated operational voltage (Ue) - max	230 V
Rated switch current	6 A
Suitable for current of main contact unit - max	8 A
Type	Accessory Accessory for miniature circuit breaker
Used with	Auxiliary contacts Accessory for miniature circuit breaker Accessory
Voltage type	AC

Technical data ETIM 9.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)		
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss13-27-14-35-02 [AKE327018])		
Device fitting		Universal
Function		Auxiliary switch
Width in number of modular spacings		0.5
Number of contacts as normally open contact		1

Number of contacts as normally closed contact		1
Number of contacts as change-over contact		0
Number of fault-signal switches		0
Rated switch current	A	6
Rated voltage	V	230
Voltage type		AC
With auto test for earth leakage function		No
Suitable for max. number of poles main contact unit (total)		2
Suitable for max. current main contact unit	A	8