

Auxiliary contact, 1N/0+1N/C

Part no. **Z-SC**
 248862
EL Number **4355534**
(Norway)

Product name	Eaton Distribution parts
Part no.	Z-SC
EAN	4015082488628
Product Length/Depth	87.5 millimetre
Product height	60 millimetre
Product width	8.75 millimetre
Product weight	0.026 kilogram
Compliances	RoHS conform
Product Tradename	None
Product Type	Distribution parts
Product Sub Type	None
Public Consumption	Yes
PDH Status	Active
Product Family Description	ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable	Yes
Additional equipment required	Auxiliary switch
Ambient operating temperature - max	60 °C
Ambient operating temperature - min	-40 °C
Assembly width	0.5
Device fitting	Auxiliary switch / relay
EL number	4355534
Equipment heat dissipation, current-dependent	0 W
Heat dissipation per pole, current-dependent	0.5 W
Main contact unit current rating - max	63 A
Number of contacts (change-over contacts)	0
Number of contacts (normally closed contacts)	1
Number of contacts (normally open contacts)	1
Number of poles at main contact unit - max	4
Number of switches (fault signal)	0
Rated operational current for specified heat dissipation (In)	3 A
Rated operational voltage (Ue) - max	230 V
Rated switch current	3 A
Rated switch current [7EF006706]	A
Rated voltage [7EF000228]	V
Static heat dissipation, non-current-dependent	0 W
Suitable for max. current main contact unit [7EF008730]	A
Voltage type	AC

Technical data ETIM 8.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)	
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecI@ss10.0.1-27-14-35-02 [AKE327013])	
Device fitting	Auxiliary switch / relay
Additional equipment	Auxiliary switch
Installed at the factory	No
Width in number of modular spacings	0.5

Number of contacts as normally open contact			1
Number of contacts as normally closed contact			1
Number of contacts as change-over contact			0
Number of fault-signal switches			0
Rated switch current		A	3
Rated voltage		V	230
Voltage type for actuating			AC
With auto test for earth leakage function			No
Suitable for max. number of poles main contact unit (total)			4
Suitable for max. current main contact unit		A	63