

Part no. Z-SV-35/3P+N-6TE
263110
EL Number 1695388
(Norway)

General specifications		
Product name		Eaton Distribution parts
Part no.		Z-SV-35/3P+N-6TE
EAN		4015082631109
Product Length/Depth		429 millimetre
Product height		38.4 millimetre
Product width		25 millimetre
Product weight		0.591 kilogram
Compliances		RoHS conform
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Product Specification Details		
Color		Other
Cross section		35 mm ²
EL number		1695388
Electric connection type		Pin
Features		Insulated Can be cut to size
Number of modular spacings		16
Number of phases		4
Number of poles		Four-pole
Pitch dimensions		0 mm
Rated conditional short-circuit current (I _q)		0 kA
Rated operational voltage (U _e) - max		415 V
Rated short-time withstand current (I _{cw})		0 kA
Rated surge voltage		4 kV
Rated uninterrupted current (I _u)		110 A
Suitable for		4 devices
Suitable for number of devices		0

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ec@ss13-27-37-13-06 [ACN992016])		
Number of phases		4
Number of poles		4
Suitable for number of devices		0
Module width	mm	0
Cross section	mm ²	35
Length	mm	429
Can be cut to size		Yes
Width in number of modular spacings		16
Rated permanent current I _u	A	110
Type of electric connection		Pin

Insulated		Yes
Rated surge voltage	kV	4
Conditioned rated short-circuit current Iq	kA	0
Max. rated operation voltage Ue	V	415
Rated short-time withstand current Icw	kA	0
Suitable for devices with N-conductor		No
Suitable for devices with auxiliary switch		No
Colour		Other