



Fuse disconnectors, 1p, 20A, 8, 5 x 31, 5

Part no. Z-SIL/20/1
 Catalog No. 263901

Similar to illustration

Technical data ETIM 7.0

| | | |
|--|----|------------------|
| Low-voltage industrial components (EG000017) / Fuse switch disconnecter (EC001040) | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnecter (ecl@ss10.0.1-27-37-14-01 [AKF058013]) | | |
| Version as main switch | | No |
| Version as safety switch | | No |
| Max. rated operation voltage Ue AC | V | 230 |
| Rated permanent current Iu | A | 32 |
| Rated operation power at AC-23, 400 V | kW | 0 |
| Conditioned rated short-circuit current Iq | kA | 10 |
| Rated short-time withstand current Icw | kA | 0 |
| Suitable for fuses | | Shape C1-C3 |
| Number of poles | | 1 |
| With error protection | | No |
| Type of electrical connection of main circuit | | Screw connection |
| Cable entry | | Other |
| Equipped with connectors | | No |
| Suitable for ground mounting | | No |
| Suitable for front mounting 4-hole | | No |
| Suitable for busbar mounting | | No |
| Type of control element | | Other |
| Position control element | | Front side |
| Motor drive optional | | No |
| Motor drive integrated | | No |
| Version as emergency stop installation | | No |
| Degree of protection (IP), front side | | IP20 |