

Block busbar 1Ph., for PLN. (1HP), Z-SI, flat blue



**Part no.**                    **Z-SV-10/N-1TE/13**  
**264917**

<b>General specifications</b>		
Product name		Eaton Distribution parts
Part no.		Z-SV-10/N-1TE/13
EAN		4015082649173
Product Length/Depth		28 millimetre
Product height		6 millimetre
Product width		232 millimetre
Product weight		0.038 kilogram
Compliances		RoHS conform
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
<b>Product Specification Details</b>		
Color		Other
Cross section		10 mm <sup>2</sup>
Electric connection type		Pin
Features		Insulated Can be cut to size
Number of modular spacings		1
Number of phases		1
Number of poles		Two-pole
Pitch dimensions		0 mm
Rated conditional short-circuit current (I <sub>q</sub> )		0 kA
Rated operational voltage (U <sub>e</sub> ) - max		415 V
Rated short-time withstand current (I <sub>cw</sub> )		0 kA
Rated surge voltage		4 kV
Rated uninterrupted current (I <sub>u</sub> )		50 A
Suitable for number of devices		19

**Technical data ETIM 9.0**

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss13-27-37-13-06 [ACN992016])		
Number of phases		1
Number of poles		2
Suitable for number of devices		19
Module width	mm	0
Cross section	mm <sup>2</sup>	10
Length	mm	28
Can be cut to size		Yes
Width in number of modular spacings		1
Rated permanent current I <sub>u</sub>	A	50
Type of electric connection		Pin
Insulated		Yes
Rated surge voltage	kV	4
Conditioned rated short-circuit current I <sub>q</sub>	kA	0

Max. rated operation voltage U <sub>e</sub>	V	415
Rated short-time withstand current I <sub>cw</sub>	kA	0
Suitable for devices with N-conductor		No
Suitable for devices with auxiliary switch		No
Colour		Other