

Additional handle, for size 3/4



Part no. **NZM3/4-XDZ**
266622

| General specifications | |
|--|--|
| Product name | Eaton Moeller series NZM operating element accessory |
| Part no. | NZM3/4-XDZ |
| EAN | 4015082666224 |
| Product Length/Depth | 200 millimetre |
| Product height | 70 millimetre |
| Product width | 55 millimetre |
| Product weight | 0.271 kilogram |
| Compliances | IEC UL/CSA RoHS conform |
| Certifications | UL (File No. E140305) UL (Category Control Number DIHS) UL listed UL489 IEC60947 CSA (Class No. 1437-01) CSA (File No. 22086) CE marking CSA certified CSA-C22.2 No. 5-09 |
| Product Tradename | NZM |
| Product Type | Accessories |
| Product Sub Type | Operating element accessory |
| Delivery program | |
| Type | Accessory Additional handle |
| Special features | Enables switching when control panel door is open |
| Frame | NZM3/4 |
| Suitable for | Power circuit breaker Switch disconnecter |
| Used with | NZM3(-4), PN3(-4), N(S)3(-4) NZM4(-4), N(S)4(-4) |
| Technical Data - Mechanical | |
| Color | Gray |
| Degree of protection / NEMA enclosure type | Other |
| Special features | Enables switching when control panel door is open |
| Design verification as per IEC/EN 61439 | |
| 10.2.2 Corrosion resistance | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | Meets the product standard's requirements. |
| 10.2.5 Lifting | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | Is the panel builder's responsibility. |

| | | | |
|-------------------------------------|--|--|--|
| 10.10 Temperature rise | | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 9.0

| | | | |
|--|--|--|-------|
| Low-voltage industrial components (EG000017) / Handle for power circuit breaker (EC000229) | | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Handle for switch devices (ecl@ss13-27-37-04-14 [AKF012019]) | | | |
| With restart blockage | | | No |
| With key lock | | | No |
| Padlock locking | | | No |
| Colour | | | Grey |
| Suitable for emergency stop | | | No |
| With extension shaft | | | No |
| Suitable for power circuit breaker | | | Yes |
| Suitable for switch disconnecter | | | Yes |
| Degree of protection (NEMA) | | | Other |